

Ref.: 413077



CONTROL VALVE, PG-77 SERIES, 1 KG/MIN, GREASE, RIGID OUTLET

High pressure grease control guns with ergonomic body and trigger designed to reduce operator hand fatigue. Manufactured in aluminium with steel insert for high pressure. Rigid outlet with 3 jaw connector Instruction book: 841801.

Technical data

Documentation

More information

Compatible fluids	Grease
Maximum free flow delivery	1 kg/min (2,2 lb/min)
Maximum outlet pressure	500 bar (7250 psi)
Operating temperature range	-10 - 70 °C (14-160 °F)
Inlet size	1/4"
Fluid inlet	1/4" BSP (F)
Fluid outlet	1/8" BSP (F)
Outlet type	Rigid tube, grease connector
Meter	No meter
Wetted materials	Zinc plated steel, Steel
Weight	0,76 kg (1,67 lb)

Technical data

Documentation

More information

[Login](#) or [register](#) to consult this content

Models

Code	Compatible Fluids	Inlet Size	Outlet Type
413077	Grease	1/4"	Rigid tube, grease connector
413082	Grease	1/4"	Z-swivel, reinforced hose tube, grease connector
413081	Grease	1/4"	Reinforced tube, grease connector
413080	Grease	1/4"	Z-swivel, rigid tube, grease connector