



# محبس جروف



| Size (Inch) | Pressure           | Standard                 | Body Material                            | Stem                                            | Wedge Disc                                  | Coating                               |
|-------------|--------------------|--------------------------|------------------------------------------|-------------------------------------------------|---------------------------------------------|---------------------------------------|
| 2.5"        | PN10 / PN16 / PN25 | DIN / BS / ANSI / Korean | Ductile iron GGG50 with WRAS FBE coating | Carbon steel galvanized / SS420 / SS304 / SS316 | Ductile iron GGG50 fully EPDM rubber coated | WRAS approved epoxy powder 300 micron |
| 3"          | PN10 / PN16 / PN25 | DIN / BS / ANSI / Korean | Ductile iron GGG50 with WRAS FBE coating | Carbon steel galvanized / SS420 / SS304 / SS316 | Ductile iron GGG50 fully EPDM rubber coated | WRAS approved epoxy powder 300 micron |
| 4"          | PN10 / PN16 / PN25 | DIN / BS / ANSI / Korean | Ductile iron GGG50 with WRAS FBE coating | Carbon steel galvanized / SS420 / SS304 / SS316 | Ductile iron GGG50 fully EPDM rubber coated | WRAS approved epoxy powder 300 micron |
| 6"          | PN10 / PN16 / PN25 | DIN / BS / ANSI / Korean | Ductile iron GGG50 with WRAS FBE coating | Carbon steel galvanized / SS420 / SS304 / SS316 | Ductile iron GGG50 fully EPDM rubber coated | WRAS approved epoxy powder 300 micron |



MADE IN CHINA