



DESIGN FEATURES



Designed for versatility and performance, handles steel and stainless steel pipes ranging from 2" to 12".



Interlocking structure between the groove roller and drive roller ensures precise control of the pipe sealing surface length.



Unique split-type hydraulic system features an independent pump and cylinder structure.



Fully enclosed pump design eliminates the need for a breather hole, reducing hydraulic oil replacement frequency and extending pump life.

SPECIFICATIONS

Fabrication Capacity	2"~12"
Max Wall Thickness	10mm
Output Speed	22RPM
Gross Weight	145kgs

STANDARD ITEMS

Drive Roller



2"-3"



3 1/2"-6"



8"-12"

Groove Roller



2"-3"



3 1/2"-6"



8"-12"

- 1 Drive roller 2"-3" (0218051/4) - 1.30kg
- 2 Drive roller 3 1/2"-6" (0218051/5) - 1.30kg
- 3 Drive roller 12"-8" (0218051/6) - 1.30kg
- 4 Groove roller 2"-3" (0218051/1) - 0.45kg
- 5 Groove roller 3 1/2"-6" (0218051/2) - 0.45kg
- 6 Groove roller 8"-12" (0218051/3) - 0.45kg
- 7 Pipe stand for 2"-12" - 6.90kg
- 8 Foot Switch - 1.50kg

7



Pipe Stand

8



Foot Switch



DRIVE UNIT

Phase: Single Power: 1100W | Voltage: 220V | Frequency: 50/60Hz

MADE IN CHINA

MODEL NO. 0218051