




رشاش حريق (سفلي / علوي) FIRE SPRINKLER

The B-Safe Fire Sprinkler is a fast response early suppression sprinkler engineered for high-performance fire protection in warehouses, storage facilities, and industrial applications. Built with a durable brass body and available in natural brass or chrome finishes, it features a fusible alloy sensitive element, NBR seal material, and is rated for rapid activation and reliable performance in demanding environments.



UPRIGHT - NATURAL BRASS



PENDENT - NATURAL BRASS



UPRIGHT - CHROME



PENDENT - CHROME

SPRINKLER (BRASS)

Model	Type	Size	K factor	Temperature	Installation space
0214001	UPRIGHT SPRINKLER	1/2"	K5.6@US k=80@CN80L/MIN	68°C up to 260°C	(H=9m) 2.4-3.7m (H≥10.5m) 2.4-3.0m
0214002	PENDENT SPRINKLER	1/2"	K5.6@US k=80@CN80L/MIN	68°C up to 260°C	(H=9m) 2.4-3.7m (H≥10.5m) 2.4-3.0m

SPRINKLER (CHROME)

Model	Type	Size	K factor	Temperature	Installation space
0214004	UPRIGHT SPRINKLER	1/2"	K5.6@US k=80@CN80L/MIN	68°C up to 260°C	(H=9m) 2.4-3.7m (H≥10.5m) 2.4-3.0m
0214005	PENDENT SPRINKLER	1/2"	K5.6@US k=80@CN80L/MIN	68°C up to 260°C	(H=9m) 2.4-3.7m (H≥10.5m) 2.4-3.0m



**BUILT FOR PERFORMANCE.
PROTECTING WHAT MATTERS.**



سابر
saber

رؤية
2030
المملكة العربية السعودية
KINGDOM OF SAUDI ARABIA