

Monitors Ambient Conditions – Efficient and Accurate

testo 608-H1 /-H2

The affordable standard testo 608-H1 hygrometer measures humidity, temperature and dewpoint.

- With dewpoint calculation td and Max/Min value display
- Humidity sensor not affected by condensation

The efficient testo 608-H2 alarm hygrometer with LED alarm function for accurate signals when limits are exceeded.

testo 608-H1

Humidity/dewpoint/temperature measuring instrument incl. battery

Part no. 0560 6081

testo 608-H2 with alarm

Humidity/dewpoint/temperature measuring instrument, incl. LED alarm, battery and calibration protocol

Part no. 0560 6082


Technical data	testo 608-H1	testo 608-H2
Meas. range	+10 to +95 %RH 0 to +50 °C -20 to +50 °C td	+2 to +98 %RH -10 to +70 °C -40 to +70 °C td
Accuracy ±1 digit	±3 %RH (+10 to +95 %RH) ±0.5 °C (at +25 °C)	±2 %RH (+2 to +98 %RH) ±0.5 °C (at +25 °C)
Oper. temp.	0 to +50 °C	-10 to +70 °C
Resolution	0.1 %RH / 0.1 °C	Measuring rate 18 s
Storage temp.	-40 to +70 °C	Dimensions 120 x 89 x 40 mm
Battery life	8736 h	Weight 168 g



Display can be read from a great distance



testo 608-H2 with LED alarm



Precision monitoring of production climate

Accessories Ordering data

ISO calibration certificate humidity, Calibration points 11.3 %RH and 75.3 %RH at +25 °C

Part no.

0520 0006