

## 3-Way Power Divider - 0°


Model PD05200A3S

### Specifications.

<b>Frequency Range</b>	0.5~20GHz	<b>Finish</b>	Gray paint
<b>Insertion Loss</b>	≤2.4dB (Above 4.8dB Split)	<b>Connector Body</b>	Passivated Stainless Steel
<b>VSWR</b>	Input ≤1.50:1 Output ≤1.50:1	<b>Housing</b>	Aluminum, 6061 T6 Clear Chem Conversion Film
<b>Isolation</b>	≥17dB	<b>Connector Pin</b>	Stainless Steel SMA-Female
<b>Amplitude Balance</b>	≤±0.5dB	<b>Solder</b>	Lead Free, RoHS Compliant
<b>Phase Balance</b>	≤±5°	<b>Operating Temperature</b>	-45°C~+85°C
<b><sup>1</sup>Power Handling</b>	Forward ≤20Watt; Reversed ≤1 Watt	<b>Operating Humidity</b>	Up to 95%,Non- Condensing
<b>Impedance</b>	50Ω	<b>Weight</b>	100g
<b>Port Connectors</b>	SMA-Female		

<sup>1</sup>Power Handling guaranteed when load's VSWR within 1.50:1.

### Mechanical Outline.



Note: Dimensions (mm / [inch]), General tolerance (±0.5 / [±0.02])