

PRODUCT DATA

TI-DEK MATT



Type

A Washable Acrylic Emulsion with a Matt Finish.

Appearance

Smooth Matt Finish.

Properties and Uses

Ti-Dek Matt has high opacity, is quick drying and is suitable for interior and exterior use.

Surface Preparation

Essential for good paint performance is a sound substrate that has been properly cleaned and prepared. On existing painted surfaces to be redecorated, a small section of paint must be removed to establish the condition of the original paint and the substrate. Where there is doubt, the paint must be removed to a sound base.

Application Instructions

These instructions are issued as an aid in determining correct surface preparation, mixing and application procedure and should be closely followed to obtain maximum service from the material.

1. New Unpainted Surfaces

e.g. Exterior one coat plaster, interior two coat plaster or Crestone ceilings.

- (a) 1st coat: Titanium White Masonry Primer.
- (b) 2nd and 3rd coat: Titanium Ti-Dek Matt.

2. Old Painted Exterior Wall Surfaces

- (a) Remove fungus growth, dust, loose and flaky material from the surface by means of a high pressure water jet. Allow the surface to dry properly.
- (b) 1st application: Titanium Anti-Fungus Wash and leave on the surface for 24 hours.
- (c) Fill imperfections with Titanium Ti-Fill.
- (d) 1st coat: Spot-prime with Titanium Masonry Primer.
- (e) 2nd and 3rd coat: Titanium Ti-Dek Matt.

<u>Application Method:</u>	Brush, roller or airless spray.
<u>Spreading Rate:</u>	± 8m ² per litre per coat on very smooth surfaces.
<u>Cleaning of Utensils:</u>	Wash immediately after use with warm soapy water.
<u>Packaging Sizes:</u>	20 L, 5 L and 1 L
<u>Colour Range:</u>	White and a variety of standard colours or any other Tint.