



◆ SPECIFICATION

Model NO.	IPRGMPL20HHE200	IPRGMPL20HHL200
Camera		
Image Sensor	1/2.7" Full HD CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP 1080P	2MP 1080P
Effective Pixels	1920(H)*1080(V)	1945(H)*1097(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG	
TV System	PAL/NTSC	
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec	
Minimum Illumination	0.01Lux	0.005Lux
S/N Ratio	≥52dB	
Scanning System	Progressive	
Video Output	Network	
Reset Button	Optional	
Lens		
Focus Length	Board Lens 3.6mm	
Focus Control	Fixed	
Lens Type	Fixed	
Pixels	2M	
Night Vision		
Infrared LED	14μ x 18PCS	
Infrared Distance	20M	
IR Status	Auto Control	
IR Power On	Auto Control	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Wireless	/	
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP	

ONVIF	Support ONVIF 2.4	
P2P	YES, Support QR Code	
POE	Optional, Support IEEE 802.3af	
Video Delay	0.3S (Within the Lan)	
Main Stream 1	2304*1296@20fps	2304*1296@20fps
Main Stream 2	1920*1080@30fps	1920*1080@30fps
Main Stream 3	1280*720@30fps	1280*720@30fps
Sub Stream 1	720*480@20fps 720*480@30fps	720*480@20fps 720*480@30fps
Sub Stream 2	/	/
Sub Stream 3	/	/
Tri Stream	352*288@20fps 352*288@30fps	352*288@20fps 352*288@30fps
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)	
Smart Phone	iPhone, iPad, Android, Android Pad	

Camera Features

Day/Night	Color/ B&W (IR-CUT)	
Intelligence function	/	/
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3DNR , White Balance, FLK(Flicker Control)	Saturation/Brightness/Contrast /Sharpness, Mirror, 3DNR , White Balance, FLK(Flicker Control)
Full Starlight	/	/
Corridor Pattern	Support	Support
Defog Mode	Support	Support
ROI	Support	Support
BLC	Support	Support
HDR	/	/
WDR	DWDR: 50dB	WDR: 96dB
Motion Detection	Support	Support
Privacy Masking	3 Rectangular Zone	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands	

Interface

Audio	Optional	Optional
Alarm	/	/
SD Card Slot	Optional, Support Max 128GB	Optional, Support Max 128GB

RS485	/	/
General		
Housing	Plastic	
Anti-cut Bracket	NO	
IR Cut Filter	YES	
Operation Temperature	-20°C ~ +60°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	
Power Source	DC12V±10%,750mA	
Dimension	90.5(W) x 80(H) x 80(D)mm	
Weight	300g	

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Tel. No.: 886-4-2561-2199

Homepage: <http://www.rgm-digital.com>

Email: sales@rgm-digital.com