



◆ SPECIFICATION

Model NO.	IPRGMPTN60HHF200	IPRGMPTN60HHL200	IPRGMPTN60HL200	IPRGMPTN60HP200
<b>Camera</b>				
Image Sensor	1/2.9" Full HD CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP 1080P	2MP 1080P	2MP 1080P	2MP 1080P
Effective Pixels	1920(H)*1080(V)	1945(H)*1097(V)	1945(H)*1097(V)	1945(H)*1097(V)
Compression	H.264/H.265/JPEG/AVI /MJPEG	H.264/H.264+/H.265/H.265+/ JPEG/AVI /MJPEG	H.264/H.264+/H.265/H.265+/ JPEG/AVI /MJPEG	H.264/H.264+/H.265/H.265+/ JPEG/AVI /MJPEG
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec			
Minimum Illumination	0.01Lux	0.005Lux	0.005Lux	0.002Lux
S/N Ratio	≥52dB	≥52dB	≥52dB	≥52dB
Scanning System	Progressive	Progressive	Progressive	Progressive
Video Output	Network	Network	Network	Network
Reset Button	Optional	Optional	Optional	Optional
<b>Lens</b>				
Focus Length	2.8-12mm	2.8-12mm	2.8-12mm	2.8-12mm
Focus Control	Manual	Manual	Manual	Manual
Lens Type	Manual	Manual	Manual	Manual
Pixels	3M	3M	3M	3M
<b>Night Vision</b>				
Infrared LED	42μ x 4PCS	42μ x 4PCS	42μ x 4PCS	42μ x 4PCS
Infrared Distance	40M	40M	40M	40M
IR Status	Auto Control	Auto Control	Auto Control	Auto Control
IR Power On	Auto Control	Auto Control	Auto Control	Auto Control
<b>Network</b>				
Ethernet	RJ-45 (10/100Base-T)	RJ-45 (10/100Base-T)	RJ-45 (10/100Base-T)	RJ-45 (10/100Base-T)
Wireless	/	/	/	/
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP			
ONVIF	Support ONVIF 2.4	Support ONVIF 2.4	Support ONVIF 2.4	Support ONVIF 2.4
P2P	YES, Support QR Code	YES, Support QR Code	YES, Support QR Code	YES, Support QR Code