



◆ SPECIFICATION

| Model NO. | IPR25HF200 | IPR25HL200 | IPR25HP200 |
|-------------------------|---|--------------------------------|--------------------------------|
| Camera | | | |
| Image Sensor | F23 | IMX307 | IMX327 |
| Main processor | Hi3516E | Hi3516C | Hi3516C |
| Resolution | 2MP 1080P | 2MP 1080P | 2MP 1080P |
| Effective Pixels | 1920(H)*1080(V) | 1945(H)*1097(V) | 1945(H)*1097(V) |
| Compression | H.264/H.264+/H.265/H.265+/JPEG/AVI / MJPEG | | |
| TV System | PAL/NTSC | | |
| Electronic Shutter Time | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec | | |
| S/N Ratio | ≥52dB | | |
| Scanning System | Progressive | | |
| Video Output | Network | | |
| Reset Button | Optional | | |
| Lens | | | |
| Focus Length | Board Lens 3.6mm | | |
| Focus Control | Fixed | | |
| Lens Type | Fixed | | |
| Pixels | 3M | | |
| Night Vision | | | |
| Infrared LED | 14μ x 20PCS | | |
| Infrared Distance | 25M | | |
| IR Status | Auto Control | | |
| IR Power On | Auto Control | | |
| Network | | | |
| Ethernet | RJ-45 (10/100Base-T) | | |
| Protocol | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP | | |
| ONVIF | Support ONVIF 2.4 | | |
| P2P | YES, Support QR Code | | |
| POE | Optional, Support IEEE 802.3af | | |
| Video Delay | 0.3S (Within the Lan) | | |
| Main Stream 1 | 1920*1080@20fps | 2048*1536@15fps | 2048*1536@15fps |
| Main Stream 2 | 1280*720@20fps | 1920*1080@30fps | 1920*1080@30fps |
| Main Stream 3 | / | 1280*720@30fps | 1280*720@30fps |
| Sub Stream 1 | 720*480@20fps | 720*480@15fps 720*480@30fps | 720*480@15fps 720*480@30fps |
| Sub Stream 2 | / | / | / |
| Sub Stream 3 | / | / | / |
| Tri Stream | 352*288@20fps | 352*288@15fps 352*288@30fps | 352*288@15fps 352*288@30fps |
| IE Brower | IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari | | |
| Smart Phone | iPhone, iPad, Android, Android Pad | | |
| Camera Features | | | |
| Day/Night | Color/ B&W (IR-CUT) | | |
| Image Config | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering | | |
| Full Starlight | / | / | / |
| Corridor Pattern | / | Support | Support |
| Defog Mode | Support | Support | Support |
| ROI | / | Support | Support |
| BLC | Support | Support | Support |
| HDR | / | / | / |
| WDR | Support | Support | Support |
| Motion Detection | Support | Support | Support |
| Privacy Masking | 3 Rectangular Zone | 3 Rectangular Zone | 3 Rectangular Zone |
| Recording Mode | NVR/NAS/CMS/Web | NVR/NAS/CMS/Web | NVR/NAS/CMS/Web |
| Language | Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands | | |
| Interface | | | |
| Audio | Optional | Optional | Optional |
| Alarm | / | / | / |
| SD Card Slot | / | Optional, Support Max 128GB | Optional, Support Max 128GB |
| RS485 | / | / | / |
| General | | | |
| Housing | IP66 | | |
| Anti-cut Bracket | YES | | |
| IR Cut Filter | YES | | |
| Operation Temperature | -20℃ ~ +60℃ RH95% Max | | |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max | | |
| Power Source | DC12V±10%,1050mA | | |
| Dimension | 157(W) x 70(H) x 66(D)mm | | |
| Weight | 650g | | |

Cantonk (guangzhou) Corporation Limited

Add. :2#, 4# Building, No. 728, Kaichuang AVE., Economic & Technological Development Zone,Luogang District,510530 Guangzhou,China

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com