



◆ SPECIFICATION

Model NO.	KDRGMSHR30HTC200FE	KDRGMSHR30HTC200F	KDRGMSHR30HTC200ESL	KDRGMSHR30HTC200ESP
Video Output Mode	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps
Camera				
Image Sensor	1/3" CMOS Sensor	1/2.9" CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Image Resolution	2M:1920*1080	2M:1920*1080	2M:1920*1080	2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto	Auto	Auto
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan	Progressive Scan
Lens				
Focus Length	Board Lens 2.8-12mm	Board Lens 2.8-12mm	Board Lens 2.8-12mm	Board Lens 2.8-12mm
Focus Control	Manual	Manual	Manual	Manual
Lens Type	Manual	Manual	Manual	Manual
Night Vision				
IR Cut Filter	YES	YES	YES	YES
Infrared LED	14μ x 24PCS	14μ x 24PCS	14μ x 24PCS	14μ x 24PCS
Infrared Distance	30M	30M	30M	30M
IR Status	AGC Auto Control	AGC Auto Control	AGC Auto Control	AGC Auto Control
Camera Features				
Starlight	/	/	YES	Super Starlight
Day/Night	YES	YES	YES	YES
OSD Menu Language	YES	YES	YES	YES
WDR	DWDR	DWDR	YES	YES
UTC	YES	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Noise Reduction	DNR	3DNR	3DNR	3DNR
Gain Control	AUTO	AUTO	AUTO	AUTO
General				
Housing	IP66	IP66	IP66	IP66
Bracket	NO	NO	NO	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,750mA	DC12V±10%,750mA	DC12V±10%,750mA	DC12V±10%,750mA
Dimension	∅ 120 x 98(H) mm	∅ 120 x 98(H) mm	∅ 120 x 98(H) mm	∅ 120 x 98(H) mm
Weight	800g	800g	800g	800g

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Tel. No.: 886-4-2561-2199 Homepage: <http://www.rgm-digital.com> Email: sales@rgm-digital.com