



◆ SPECIFICATION

Model NO.	KBRGMCV25HTC200F	KBRGMCV25HTC200FS	KBRGMCV25HTC200ESL	KBRGMCV25HTC200ESP
Video Output Mode	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps
<b>Camera</b>				
Image Sensor	1/2.9" CMOS Sensor	1/2.9" SONY CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Image Resolution	2M:1920*1080	2M:1920*1080	2M:1920*1080	2M:1920*1080
TV System	PAL/NTSC			
Electronic Shutter	Auto	Auto	Auto	Auto
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan	Progressive Scan
<b>Lens</b>				
Focus Length	Board Lens 3.6mm	Board Lens 3.6mm	Board Lens 3.6mm	Board Lens 3.6mm
Focus Control	Fixed	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed	Fixed
<b>Night Vision</b>				
IR Cut Filter	YES			
Infrared LED	14μ x 18PCS			
Infrared Distance	20M			
IR Status	CDS Auto Control	CDS Auto Control	Smart IR control	Smart IR control
<b>Camera Features</b>				
Starlight	/	/	YES	Super Starlight
Day/Night	YES	YES	YES	YES
OSD Menu Language	YES	YES	YES	YES
WDR	DWDR	DWDR	YES	YES
UTC	YES	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Noise Reduction	3DNR	3DNR	3DNR	3DNR
Gain Control	AUTO	AUTO	AUTO	AUTO
<b>General</b>				
Housing	IP66			
Bracket	YES			
Operation Temperature	-10℃ ~ +60℃ RH95% Max			
Storage Temperature	-20℃ ~ +60℃ RH95% Max			
Power Source	DC12V±10%,550mA			
Dimension	151(W) x 64(H) x 65.5(D)mm			
Weight	700g			

**RGM Digital**

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Tel. No.: 886-4-2561-2199

Homepage: <http://www.rgm-digital.com> Email: [sales@rgm-digital.com](mailto:sales@rgm-digital.com)