



◆ SPECIFICATION

| Model NO. | KBRGMCV60HTC200FE | KBRGMCV60HTC200F | KBCV60HTC200ESL | KBCV60HTC200ESP |
|------------------------|-----------------------------|-----------------------------|--|--|
| Video Output Mode | AHD/TVI/CVI: 2M@30fps/25fps | AHD/TVI/CVI: 2M@30fps/25fps | AHD/TVI/CVI: 2M@30fps/25fps | AHD/TVI/CVI: 2M@30fps/25fps |
| Camera | | | | |
| Image Sensor | 1/3" CMOS Sensor | 1/2.9" CMOS Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor |
| Image Resolution | 2M:1920*1080 | 2M:1920*1080 | 2M:1920*1080 | 2M:1920*1080 |
| TV System | PAL/NTSC | PAL/NTSC | PAL/NTSC | PAL/NTSC |
| Electronic Shutter | Auto | Auto | Auto | Auto |
| Scanning System | Progressive Scan | Progressive Scan | Progressive Scan | Progressive Scan |
| Lens | | | | |
| Focus Length | 2.8-12mm Manual Zoom Lens | 2.8-12mm Manual Zoom Lens | 2.8-12mm Manual Zoom Lens | 2.8-12mm Manual Zoom Lens |
| Focus Control | Manual | Manual | Manual | Manual |
| Lens Type | Manual | Manual | Manual | Manual |
| Night Vision | | | | |
| IR Cut Filter | YES | YES | YES | YES |
| Infrared LED | 42μ x4PCS | 42μ x4PCS | 42μ x4PCS | 42μ x4PCS |
| Infrared Distance | 40M | 40M | 40M | 40M |
| IR Status | AGC Auto Control | AGC Auto Control | AGC Auto Control | AGC Auto Control |
| Camera Features | | | | |
| Starlight | / | / | YES | Super Starlight |
| Day/Night | YES | YES | YES | YES |
| OSD Menu Language | YES | YES | YES | YES |
| WDR | DWDR | DWDR | YES | YES |
| UTC | YES | YES | YES | YES |
| White Balance | AUTO / MANUAL | AUTO / MANUAL | AUTO / MANUAL | AUTO / MANUAL |
| Noise Reduction | DNR | 3DNR | 3DNR | 3DNR |
| Gain Control | AUTO | AUTO | AUTO | AUTO |
| General | | | | |
| Housing | IP66 | IP66 | IP66 | IP66 |
| Bracket | YES | YES | YES | YES |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max | -10℃ ~ +60℃ RH95% Max | -10℃ ~ +60℃ RH95% Max | -10℃ ~ +60℃ RH95% Max |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max | -20℃ ~ +60℃ RH95% Max | -20℃ ~ +60℃ RH95% Max | -20℃ ~ +60℃ RH95% Max |
| Power Source | DC12V±10%,750mA | DC12V±10%,750mA | DC12V±10%,750mA | DC12V±10%,750mA |
| Dimension | 220(W) x 80(H) x 80(D)mm | 220(W) x 80(H) x 80(D)mm | 220(W) x 80(H) x 80(D)mm | 220(W) x 80(H) x 80(D)mm |
| Weight | 1.4Kg | 1.4Kg | 1.4Kg | 1.4Kg |

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Tel.No.: 886-4-2561-2199 Homepage: <http://www.rgm-digital.com> Email: sales@rgm-digital.com