



◆ SPECIFICATION

| Model NO. | S200GS | S200GD |
|------------------------------|--|--------|
| Basic Parameters | | |
| Driver Signal | 12V | |
| Driver Voltage | 24V | |
| Movement | Single | Dual |
| Passing Speed | 35 Persons/Min | |
| Traffic | Unidirectional/Bidirectional | |
| Open & Close Time | 0.5-1s | |
| Material | 304 Stainless | |
| Channel Width | ≤600mm | |
| Swing Arm | 270mm/acrylic | |
| Card Reader | Support | |
| Counting People | Optional | |
| Illegal infiltration | Support | |
| Anti-pinch | Infrared/Mechanical | |
| Infrared | 3 Pairs | |
| Interface | | |
| RS485 | RS485 electrical standard,communication distance: <1200 meters | |
| Input Port | Switch Signal(NO NC COM) | |
| Network Port | Optional | |
| General Specification | | |
| Power | 220V±10% 50Hz 110V±10% 60Hz(optional) | |
| Working Temperature | -30℃~60℃/10~95% | |
| Device Size | 1200*300*980mm | |
| Package Size | 1210*310*1000mm | |

| | | |
|----------------|-------|-------|
| Package Weight | 150KG | 225KG |
|----------------|-------|-------|

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Tel.No.: 886-4-2561-2199

Email: sales@rgm-digital.com

Homepage: <http://www.rgm-digital.com>