



(The picture is for reference only)

Descriptions

It has the characteristics of seamless, perfect display, long lifespan, fast frame change, high refresh rate, good uniformity, wide viewing angle, high gray level and natural color reproduction. It is widely used in the command & dispatch, security monitoring, video conference, demonstrations and various indoor conference room display areas.

Features

- * It can be used for real-time scene monitoring, various advertising playback.
- * It is seamlessly spliced without no visual black seams at all.
- * The display module is flexible, flat, curved with smooth splicing.
- * DC low voltage power supply; natural heat dissipation, no fan and no operation noise.
- * When a failure happens, user is only required to maintain a single LED lamp or a single module at very low maintenance cost but pretty high speed.

- * Support picture correction. The Gamma correction adopted enables pixel-by-pixel brightness color correction.
- * Support intelligent light control for brightness adjustment, bringing higher picture comfort levels, energy and electricity saving.
- * With ultra-wide viewing angle display. Audience at a larger viewing range can watch clearly at any angle.
- * With ultra-high refresh rate, good picture coherence and high picture fluency.
- * The picture is delicate and realistic, and the gray level is still excellent under low brightness.
- * Support ultra HD display. Unique image quality enhancement technology effectively improves image clarity, making high-speed picture smooth without image tail.
- * Support to integrate 3D, touch screen and somatosensory games for more entertainment and interactivity.
- * Wireless connection makes the rear panel clean and safe.
- * Hard connection. Support hot plug for convenience and efficiency.

Module Specifications

LED package form	1010 black light
Pixel pitch	1.25mm
Resolution	640000 pixels / m ²
Lamp/IC	NATIONSTAR / PWM
Pixel composition	1R1G1B
Module resolution	160x135
Module size (mm)	200x168.75
Panel resolution	480 × 270
Panel size (mm)	600 * 337.5
Panel weight	7.8Kg per panel
Operating voltage	DC + 4.2V

Main Specifications

Best viewing distance	≥ 3.75m
Horizontal viewing angle	≥160 °
Vertical viewing angle	≥160 °
Maintenance method	Front maintenance
Graphics card	DVI / HDMI / DP
Video signals	Compatible with PAL / NTSC / SECAM system, support S-Video; VGA; RGB; Composite Video; SDI; DVI; RF; RGBHV; YUV; YC, etc.
Control method	Synchronous control
Drive device	Constant current
Refresh rate	3840Hz
Refresh frame frequency	≥60Hz
Scanning method	27s
Brightness	200-800CD / m ²
Grayscale	12/14 / 16bit
Contrast	10000: 1
Attenuation rate	≤15%
(after working for 3 years)	
Brightness adjustment method	Automatic / manual: 1-100%
Computer operating system	WIN98 / 2000 / WIN XP / WIN Vista / WIN7
MTBF	≥10000H
Lifespan	≤100000H
Failed rate	≤1/100000 and no continuous failed pixels
Software	Professional LED video wall programming software
Mounting box specifications	Die-casting aluminum cabinet
Brightness uniformity	≥98%
Protection level	IP5X

Electrical Specifications

Operating voltage (AC)	220V ± 10% / 50Hz or 110V ± 10% / 60Hz
Average power consumption	179W / m ²
Maximum power consumption	538W / m ²
Storage temperature	-35 ° ~ + 85 °
Operating temperature	-10 ° ~ + 40 °