



◆ SPECIFICATION

<b>Model</b>	<b>PTRGMDK10XH7C500NS</b>
<b>Camera</b>	
Image Sensor	1/2.7" OV 5MP CMOS Sensor
Image Resolution	5MP
TV System	PAL/NTSC
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	30°/S
Horizontal Rotation Range	0°~200°
Tilt Rotation Speed	25°/S
Tilt Rotation Range	-45°~40°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	5.1mm-51mm
Focus Control	10X Optical Zoom
<b>Night Vision</b>	
Infrared LED	6PCS Array IR LEDs + 2PCS Laser Lamp
IR Range	100m
Day-night mode	AUTO
<b>Communication</b>	
UTC	Support

RS485	Support
<b>Interface</b>	
Audio	/
Alarm	/
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/2A
Lightning Protection	Transient voltage 6000V
Size of Package (LxWxH)	39.6x19.6x16(cm)
Weight	3Kgs

**RGM Digital**

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Email: sales@rgm-digital.com

Tel. No.: +886-955-5181-22

Homepage: <http://www.rgm-digital.com>