



◆ SPECIFICATION

Model	PTRGM5EH22XHHL200
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Image Resolution	2MP
Compression	H.265/H.264
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	120°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	60°/s
Tilt Rotation Range	0°~93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	3.9mm-85.5mm
Focus Control	22X Optical Zoom
Night Vision	
Infrared LED	7PCS Array IR LEDES + 2PCS Laser Lamp
IR Range	150m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	2304*1296@20fps
Main Stream2	1920*1080@30fps
Sub Stream1	800*448@30fps
Sub Stream2	704*576@30fps
Sub Stream3	640*360@30fps
Sub Stream4	352*288@30fps
Interface	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	/
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V 2A/3A

Lightning Protection	Transient voltage 6000V
Dimension	25x21.5x41(cm)
Weight	4.9Kgs

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Email: sales@rgm-digital.com

Homepage: <http://www.rgm-digital.com>