



◆ SPECIFICATION

Model	PTRGM10GH20XHS500
<b>Camera</b>	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H.265
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	200°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	100°/s
Tilt Rotation Range	0°~90°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	4.7mm-94mm
Focus Control	20X Optical Zoom
<b>Night Vision</b>	
Infrared LED	∅ 42 x 10PCS IR LEDES + 5PCS LED Laser
IR Range	240m
Day-night mode	AUTO
<b>Network</b>	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	2560*1920@20fps
Main Stream2	2560*1440@25fps
Main Stream3	2304*1296@25fps
Main Stream4	1920*1080@25fps
Main Stream5	1280*720@25fps
Main Stream6	640*512@25fps
Sub Stream1	800*448@25fps
Sub Stream2	704*576@25fps
Sub Stream3	640*360@25fps
Sub Stream4	352*288@25fps
<b>Interface</b>	
Audio	Optional
Alarm	Optional
SD Card Slot	/
POE	/

<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~+40° Outdoor: -40°~+60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	33x33x52(cm)
Weight	13.7Kgs

**RGM Digital**

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Email: sales@rgm-digital.com

Homepage: <http://www.rgm-digital.com>