



◆ SPECIFICATION

Model	PTRGM4B18XIHHL200
<b>Camera</b>	
Image Sensor	1/2.8" SONY Low Illumination CMOS Sensor
Horizontal Resolution	2MP
Compression	H.264/H.264+/H.265/MJPEG
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	80°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	45°/S
Tilt Rotation Range	-45°~40°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	5.35mm-96.3mm
Focus Control	18X Optical Zoom
<b>Night Vision</b>	
Infrared LED	No, 8 PCS matrix high power warm light
IR Range	/
Day-night mode	/
<b>Network</b>	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	1920*1080@30fps
Main Stream2	1280*720@30fps
Sub Stream1	800*448@30fps
Sub Stream2	704*576@30fps
Sub Stream3	640*360@30fps
Sub Stream4	352*288@30fps
<b>AI Function</b>	
Smart Analytic	3D Human Tracking、 Intrusion Detection、 Line Cross Detection、 Alarm Detection
Tracking effective range	5~45M Speed: 3~12KM/h
<b>Interface</b>	
Audio	2-Way Audio
Alarm	/
SD Card Slot	/
POE	Optional
<b>General</b>	

Weatherproof	IP66
Operating Temperature	-40°~ +70°
Operating Humidity	≤90% Non Condensing
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	18.5x 18.5 x 28.8 (cm)
Weight	2.2Kgs

**RGM Digital**

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Email: [sales@rgm-digital.com](mailto:sales@rgm-digital.com)

Homepage: <http://www.rgm-digital.com>