



◆ SPECIFICATION

| Model | PTRGMDKIHHL200 |
|---------------------------|---|
| Camera | |
| Image Sensor | 1/2.8" SONY Low Illumination CMOS Sensor |
| Horizontal Resolution | 2MP |
| Compression | H.264/H.264+/H.265/MJPEG |
| S/N Ratio | >50db |
| PTZ | |
| Horizontal Rotation Speed | 30°/S |
| Horizontal Rotation Range | 0°~200° |
| Tilt Rotation Speed | 25°/S |
| Tilt Rotation Range | -45°~40° |
| Preset Points | 220 |
| Guard Tours | 3 groups |
| Guard Points | Max.16 points |
| Lens | |
| Focus Length | 4mm |
| Focus Control | Fixed |
| Night Vision | |
| Infrared LED | 35μx6PCS |
| IR Range | 80m |
| Day-night mode | AUTO |
| Network | |
| Network protocol | TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P |
| ONVIF | Support |
| Network interface | Built-in RJ45 network interface, support 10M/100M IP DATA |
| Main Stream1 | 1920*1080@30fps |
| Main Stream2 | 1280*720@30fps |
| Sub Stream1 | 800*448@30fps |
| Sub Stream2 | 704*576@30fps |
| Sub Stream3 | 640*360@30fps |
| Sub Stream4 | 352*288@30fps |
| AI Function | |
| Smart Analytic | Human Tracking、Intrusion Detection、Line Cross Detection、Alarm Detection |
| Tracking effective range | 3~15m |
| Interface | |
| Audio | 2-Way Audio |
| Alarm | / |
| SD Card Slot | / |
| POE | Optional |
| General | |

| | |
|-----------------------|-------------------------|
| Weatherproof | IP66 |
| Operating Temperature | -40°~ +60° |
| Operating Humidity | ≤90% Non Condensing |
| Power | DC12V/2A |
| Lightning Protection | Transient voltage 6000V |
| Dimension | 39.6x19.6x16(cm) |
| Weight | 1.6Kgs |

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Email: sales@rgm-digital.com

Homepage: <http://www.rgm-digital.com>