



◆ SPECIFICATION

<b>Model</b>	<b>PTRGMDAHTC5004XNS</b>
<b>Camera</b>	
Image Sensor	1/2.7" 5MP CMOS Sensor
Image Resolution	5MP
TV System	PAL/NTSC
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	20°/S
Horizontal Rotation Range	0°~350°
Tilt Rotation Speed	25°/s
Tilt Rotation Range	0°~70°
Preset Points	220
Guard Tours	8 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	2.8mm-12mm
Focus Control	4X Optical Zoom
<b>Night Vision</b>	
Infrared LED	∅ 35x4PCS
IR Range	35m
Day-night mode	AUTO
<b>Communication</b>	
UTC	Support

RS485	Support
<b>Interface</b>	
Audio	/
Alarm	/
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V 2A
Lightning Protection	Transient voltage3000V
Size of Package (LxWxH)	14x14x13(cm)
Weight	1.1Kgs

**RGM Digital**

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Email: sales@rgm-digital.com

Homepage: <http://www.rgm-digital.com>