



◆ SPECIFICATION

Model	PTRGMDK10XHHL200
<b>Camera</b>	
Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
Horizontal Resolution	2MP
Compression	H.264
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	30°/S
Horizontal Rotation Range	0°~180°
Tilt Rotation Speed	25°/S
Tilt Rotation Range	-45°~40°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	5.1mm-51mm
Focus Control	10X Optical Zoom
<b>Night Vision</b>	
Infrared LED	4PCS Array IR LEDES + 2PCS Laser Lamp
IR Range	100m
Day-night mode	AUTO
<b>Network</b>	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	2304*1296@20fps
Main Stream2	1920*1080@30fps
Sub Stream1	800*448@30fps
Sub Stream2	704*576@30fps
Sub Stream3	640*360@30fps
Sub Stream4	352*288@30fps
<b>Interface</b>	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing

Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	39.6x19.6x16(cm)
Weight	3Kgs

**RGM Digital**

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Email: [sales@rgm-digital.com](mailto:sales@rgm-digital.com)

Homepage: <http://www.rgm-digital.com>