



16 Port Gigabit Layer2 Managed PoE Switch PSRGM3016GS

- ✓ AI Smart POE Switch
- ✓ 16*1000Mbps RJ45 port
- ✓ 2*1000Mbps SFP port

- Supports the management of Apollo cloud.
- Standard mode: All ports communicate freely.
- AI VLAN: Avoid the internet storm and enhance the network ability.
- AI Extend: Extend 250M transmission.
- AI PoE: Automatic self-checking.



RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central
District, Taichung City, Taiwan
Tel. No.: 886-4-2561-2199
Homepage: www.rgm-digital.com
sales@rgm-digital.com



TECHNICAL SPECIFICATION

Switch	PSRGM2010G
Network Standard	IEEE 802.3i IEEE 802.3u IEEE 802.3x IEEE 802.3ab IEEE 802.3af IEEE 802.3at
Port	24 10/100/1000Mbps RJ45 port 2 gigabit SFP 1 Console
PoE	16↑10/100/1000Mbps RJ45 port Support PoE + max 250W Single port max 46W
LEDs	18 Link/Act LEDs 16 POE LEDs 1 SYS LED 1 Power LED
Performance	Forwarding mode: store and forward Bandwidth : 36Gbps Packet forwarding rate : 23.8Mpps 8K MAC address table
Lightning Protection	6KV
Input power	100-240V/50-60Hz
Environmental	Operating Temperature: 0~40°C Storage Temperature : -40~70°C Operating Humidity: 10%~90%, non-condensing Storage Humidity: 5%~95%, non-condensing
Dimensions	Size (LxWxH) : 440mm×180mm×44mm