

46 inch 3.5mm Bezel LED Video Wall MO-RGM46LED



High Quality CCTV Solutions

- ✓ Narrow Bezel Width
- ✓ 24/7 Usage
- ✓ Multiple Inputs
- ✓ Multiple Configuration
- ✓ Intelligent Split Screen
- ✓ 100.000 Hours Lifespan



Automatic Color & Brightness Calibration

Built-in mosaic controller

Eco-Friendly Power Timer



Infrared & Capacitive
Touch



Windows Ready

178°

Wide-View Angle

- ✓ Operating system (OS): Windows & Android
- ✓ 3D Processing Kernel
- ✓ IPS Commercial Grade Panel



RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central
District, Taichung City, Taiwan
Tel. No.: 886-4-2561-2199
Homepage: www.rgm-digital.com
sales@rgm-digital.com



TECHNICAL SPECIFICATION

TECHNICAL SPECIFICATION	
Model	MO-RGM46LED
Bezel	3.5mm
Chip	Hi3516D+Sony IMX327
LCD Panel	Max Resolution Support: 1920×1080(H×V)
	Pixel Pitch: 0.53025 (H) ×0.53025 (V)
	Brightness (nits): 500 (cd/ m)
	Contrast: 4000:1
	Response Time 8ms
	Color: 16.7M
Image	Visual Angle: (H/V) 178°(H) / 178°(V)
	Contrast; 16 : 9
	Picture quality compensation: LTI、CTI
	Motion compensation: AUTO MOVE
	Filter: 3D comb filtering digital noise reduction
Video Wall Controller (Built-in each Screen)	Video format: PAL、NTSC
	Computer centralized control interface: RS232
Structure	Border dimension: Top: 3.3mm; bottom :2.0mm; Left: :3.3mm; Right: 2.0mm
	Net weight: 25kg
	Shell material: Metal shell, anti-static, anti-magnetic, anti-strong electric field interference
	Installation way: Wall mount, floor standing mount, hanging mount
Configuration	
Signal Source	Display Port (DP): 3840x2160@30Hz、 3840x2160@20Hz、 3840x2160@25Hz
	HDMI: 480p、 576p、 720p、 1080i、 1080p、 2160p
	DVI: 480p、 576p、 720p、 1080i、 1080p
	Input port:
	Display Port: DP×1
	PC-RGB: 15 D-SUB×1
	HDMI: HDMI×1
	DVI: DVI×1
	Output:
	RS232: 1
Display Port: DP×1	