



GLASSGO PAINTS

## QD ENAMEL DATA SHEET

DATE ISSUED: 2018-01-31

### SECTION 1. MANUFACTURER

Glassgo paints

### SECTION 2. DESCRIPTION

Product Name: QD Enamel

### SECTION 3. PRODUCT BENEFITS AND USES

Quick dry enamel is an economical high gloss coating designed for industrial applications. For use on mild steel surfaces on various products for the likes of scaffolding, palisade fencing, wheel rims, garden furniture and many more lighter industrial products.

### SECTION 4. PREPERATION

Must be used on well primed mild steel surfaces. Can be used over qd and etch primed surfaces.

### SECTION 5. TECHNICAL DATA

Type	: Synthetic alkyd enamel
Gloss Level	: high gloss
Re Coating Time	: Within 2 hours
Viscosity	: 60 KU
Practical Spread Rate	: 4 - 6 m <sup>2</sup>
Specific Gravity	: 0.98 depending on colour
Solid by volume	: 28% depending on colour
Solid by Mass	: 24.94 depending on colour
Drying Time	: Surface dry 20 minutes : Hard dry 24 hours
Recommended DFT	: 20-30 microns.2 Coats Recommended
Flashpoint	: 21 C

### SECTION 6. COLOUR RANGE

Wide selection of standard colours

### SECTION 7. METHODS OF APPLICATION

Conventional or airless spray recommended

### SECTION 8. THINNING

Glassgo enamel thinner

### SECTION 9. PRECAUTION

Use in well ventilated areas, safety glasses and respirators to be worn.

### SECTION 10. FLASHPOINT

21 Degrees C

### SECTION 11. PACKAGING

1L, 5L, 20L, 200L

