



GLASSGO PAINTS

GLASSGO POLYURETHANE COLOURS DATA SHEET

Name: Glassgo Polyurethane colours

Code:PU

Date Issued: 2018/06/01

SECTION 1. MANUFACTURER

Paintworx Manufacturing (Pty)Ltd
Registration No. 2005/005928/07

SECTION 2. DESCRIPTION

Product Name : Polyurethane colours

GL- : PU

Date Issued : 2018/06/01

SECTION 3. PRODUCT BENEFITS

Good adhesion.
Good general durability.
High gloss, Good strength
Good resistance to oil spills and splashes and
Certain chemicals (petrol, diesel etc)

SECTION 4. PREPERATION

Use Glassgo MS primers as a first coat. Ensure all surfaces are clean , free from dust oil or any other contaminants.

SECTION 5. TECHNICAL DATA

Type : Hydroxy twin pack
Gloss Level : *High*
Re Coating Time : 24 hours
Viscosity : 95 - 105ku
Practical Spread Rate : 4 - 6 m²
Specific Gravity : 0.98 - 1.16 depending on colour
Solid by volume : Base 30 - 32% mixed
Solid by Mass : Base 31 -33% mixed
Drying Time : Surface 15-20 minutes
Hard 24 hour
Recommended DFT: +/- 50 - 80 microns 2 coats

SECTION 6 . COLOUR RANGE

All.

SECTION 7. METHODS OF APPLICATION

Spray and brush.

SECTION 8. THINNING

4 part polyurethane paint, 1 part polyurethane hardener, 1 part polyurethane thinners.

SECTION 9. CLEAN UP

Polyurethane thinners.

SECTION 10. PRECAUTION

Use in well ventilated areas.
Highly flammable.
Goggles and respirators to be worn in confined areas.
Avoid skin contact.

SECTION 11. PACKAGING

1 Litre
5 Litre
25 Litre
200 Litre

SECTION 12. FLASHPOINT

21 Degrees Celsius.