



GLASSGO PAINTS

ROOF PAINT DATA SHEET

DATE ISSUED: 2018-01-31

SECTION 1. MANUFACTURER

Glassgo Paints

SECTION 2. DESCRIPTION

Product name: Roof paint

SECTION 3. PRODUCT BENEFITS

A high-quality roof paint with good adhesion to tin roof, tiles, concrete and paving bricks. UV resistant for long lasting protection.

SECTION 4. PREPERATION

Ensure that all surfaces are clean, free from dust oil, grease or any other contaminants.

SECTION 5. TECHNICAL DATA

Type	: Acrylic polymer
Gloss Level	: Semi sheen
Re Coating Time	: 5 - 6 Hours
Viscosity	: 80 - 90 ku
Practical Spread Rate	: 4 - 6 square meters
Specific Gravity	: 1.1 - 14.23 dep on colour
Solids by volume	: 22.63%
Solids by Mass	: 33.30%
Drying time	: Surface dry 30 minutes
Recommended DFT	: 35 microns per coat (2coats reccomended)
Flashpoint	: Non-flammable

SECTION 6. COLOUR RANGE

Black, brown, charcoal, cosmos blue, dove grey, green, hunters green, red, terracotta, white

SECTION 7. METHODS OF APPLICATION

Brush, roller or airless spray

SECTION 8. THINNING

Only for spraying max 20 % water

SECTION 9. CLEAN UP

Water

SECTION 10. PRECAUTION

Use in well ventilated areas

SECTION 11. PACKAGING

1L, 5L, 20L, 200L.

