



GLASSGO PAINTS

UNIVERSAL UNDERCOAT DATA SHEET

DATE ISSUED: 2018-01-31

SECTION 1. MANUFACTURER

Glassgo Paints

SECTION 2. DESCRIPTION

Product name: Universal undercoat

SECTION 3. PRODUCT BENEFITS

Improves intercoat adhesion between primer and top coats. Can be overcoated with alkyd based or emulsion base top coats. Can be used over previously painted or primed substrates.

SECTION 4. PREPERATION

Ensure that substrates are suitably prepared or primed and free from dust, oil and any other contaminants.

SECTION 5. TECHNICAL DATA

Type	: Medium oil system
Gloss Level	: Satin
Re Coating Time	: 8 Hours
Viscosity	: RFU
Practical Spread Rate	: 4 - 6 Squares per L
Specific Gravity	: 1.35 - 1.43
Solids by volume	: 45%
Solids by Mass	: 64%
Drying time	: 4 Hours
Recommended DFT	: 20 microns per coat
Flashpoint	: 37%

SECTION 6. COLOUR RANGE

White

SECTION 7. METHODS OF APPLICATION

Brush or roller

SECTION 8. THINNING

Not recommended

SECTION 9. CLEAN UP

Lacquer thinner

SECTION 10. PRECAUTION

Use in well ventilated areas, goggles and respirators to be worn where necessary.

SECTION 11. PACKAGING

1L, 5L, 20L, 200L

