



GLASSGO PAINTS

CONTRACTORS PVA DATA SHEET

DATE ISSUED: 2018-01-31

SECTION 1. MANUFACTURER

Glassgo paints

SECTION 2. DESCRIPTION

Product Name: Contractors pva

SECTION 3. PRODUCT BENEFITS

A good quality contractors pva
For use on newly plastered walls, interior, exterior and as undercoat

SECTION 4. PREPERATION

Ensure that all surfaces are clean, free from dust, oil, grease or any other contaminants before painting.

SECTION 5. TECHNICAL DATA

R Type	: Styrene Acrylic Polymer
Gloss level	: Matt
Coating Time	: 5 - 6 Hours
Viscosity	: 90 - 100 ku
Practical Spread Rate	: 4 - 6 m ²
Specific Gravity	: 1.34
Solid by volume	: 32%
Solid by Mass	: 44%
Drying Time	: Surface dry 30 minutes
Recoating time	: 2 Hours
Recommended DFT	: 30 - 35 micron per coat. 2 Coats Recommended

SECTION 6. COLOUR RANGE

White only

SECTION 7. METHODS OF APPLICATION

Brush, Roller and airless spray

SECTION 8. THINNING

Not Recommended

SECTION 9. CLEAN UP

Water

SECTION 10. PACKAGING

1L, 5L, 20L, 200L

SECTION 11. FLASHPOINT

Non - flammable.

