'Bp' P.C.D. m T2 'Sh, Sn'. **BASE PLATE DETAIL** 4 NOS. FOUNDATION BOLTS NUT-3 NOs. F.G.L. F.G.L. 1 NO. PLAIN WASHER Ø63 FLEXIBLE PVC PIPE BASE PLATE (FOR CABLE ENTRY) 'Tk' T1 'Fal' æ R.C.C. (GR.) P T2 **FOUNDATION BOLT DETAIL** HINGE WELDED TO DOOR COVER POLE HINGE WELDED DETAIL OF CIVIL FOUNDATION **RIVETING** DOOR PIN HINGES 占 100 HINGE WELDED TO DOOR COVER NAME PLATE POLE HINGE WELDED **RIVETING** M10 BOLT 'De HINGE ARRANGEMENT DETAIL "Z" FOR EARTHING 250 "B"

TOLERANCES:-

DIAMETERS A/F

REV. NO.

DATE

POLE TOTAL LENGTH

POLE STRAIGHTNESS

REVISION DESRIPTION

± 2.5 %

± 1.2 %

± 0.3 %

CHKD

DRWN

FGL

This drawing is property of "BAJAJ ELECTRICALS LTD."

& must returned on request. It is submitted as confidential information in connection with enquiry, tenders, orders or contracts. It is not to be used for any other purpose or order nor may it be re-copied or lent

ELEVATION

without our authority in writing.

GENERAL NOTES:-

- 1. ALL DIMENSIONS ARE IN M.M.
- 2. DESIGN STANDARD BS EN 40-3-1&3
- 3. DESIGN CRITERIA:
 - 3.1. BASIC WIND SPEED IS: 875 PART III: 2015
 - 3.2. DESIGN LIFE 25 YEARS.
 - 3.3. TERRAIN CATEGORY 2
 - 3.4. TOPOGRAPHY FLAT
- 4. MATERIALS:
 - 4.1. SHAFT: HOT ROLLED STEEL PLATE CONFORM TO IS-2062/ BSEN 10025 OR EQUIVALENT GRADE.
 - 4.2. FLANGE/GUSSETS/DOOR STIFFENER : AS PER IS-2062/ BSEN 10025 OR EQUIVALENT GRADE.
 - 4.3. FOUNDATION BOLTS: EN-8 GRADE
- 5. FINISHING: HOT DIP GALVANIZED TO BS EN ISO 1461.
- 6. TOLERANCES SHALL BE AS PER BS EN 40-2 UNLESS OTHERWISE SPECIFIED IN THE DRAWING
- 7. MAKE OF THE POLE "BAJAJ".
- 8. THIS HAS TO BE READ IN CONJUNCTION WITH FINAL OFFER

FOUNDATION NOTES:-

- 1. ASSUMED S.B.C. 10 T/M² (MINIMUM)
- 2. GRADE OF STEEL REINFORCEMENT Fe 415 / Fe 500
- 3. CLEAR COVER TO REINFORCEMENT 50 MM
- 4. CONCRETE VIBRATED
- 5. USE SHUTTERING

Sr. No.	Abbreviation	Parameters	Detail					
Α	POLES							
1	Н	Height of pole.	5 Mtr.					
2	Т	Pole Top A/F.	70mm					
3	В	Pole Bottom A/F.	130mm					
4	Tk	Shaft Thickness.	3mm					
5	Dh	Door Height	500mm					
6	De	Door elevation	500mm					
7	Вр	Base plate dim.	200x200x12mm					
8	Sh	Slot / Hole dim.	20x34mm					
9	Sn	No. of slot/holes.	4 nos.					
10	PCD	PCD	200mm					
11	S	Pole Shape/sides	Octagonal					
С	FOUNDATION BOLT							
1	Fal	Foundation Bolt Detail	EN8 Grade, M16x450mm					
1			J Type					
2	Th	Threaded Length	80mm					
D	FOUNDATION BLOCK DETAIL							
1	Fp	Total Depth	1300mm					
2	Fd	Planting Depth	1100mm					
3	Fa	Elevation above ground	200mm					
4	Fw	Width	400mm					
5	T1	Bar dia & qty in nos.	Ø12mm - 04 nos.					
6	T2	Bar dia & CTC spacing	Ø8mm at 190 C/C					
7	RCC (GR)	Concrete Grade	M-20					

		/	RCC (GR)	Concrete Grade	M-20	
	CLIENT:	ļ				
	PROJECT:	STREET LIGHTING				
	DEALER:					
	MANUFACTURER:	SAJAJ Electricals		BAJAJ ELECTRICALS	LIMITED	
	TITLE:	INDICATIVE GENERAL ARRANGEM		MENT & FOUNDATION DRAWING OF 5M OCTAGONAL		DATE:
		POLE				15-02-2024
	DRWN BY:	MTP	PROJECT CODE:	DRG NO.		SHEET:
	DSGD BY:	SK	STD			01 of 01
	CHKD BY:	UM	DESIGN CODE:	PL-OP-24-STE	0-5M HS-001	REV. NO.:
APPRD	APPRD BY:	SA				00
			· ·			