



NOTES:-

1. ALL DIMENSIONS ARE IN M.M.
2. DESIGN STANDARD BS EN 40-3-1&3
3. DESIGN CRITERIA :
 - 3.1. BASIC WIND SPEED - IS: 875 PART III : 2015
 - 3.2. DESIGN LIFE - 25 YEARS.
 - 3.3. TERRAIN CATEGORY - 2
 - 3.4. TOPOGRAPHY - FLAT
4. MATERIALS:
 - 4.1. SHAFT : HOT ROLLED STEEL PLATE CONFORM TO IS-2062/ BSEN 10025 OR EQUIVALENT GRADE.
 - 4.2. FLANGE/GUSSETS/DOOR STIFFENER : AS PER IS-2062/ BSEN 10025 OR EQUIVALENT GRADE.
 - 4.3. FOUNDATION BOLTS: EN-8 GRADE
5. FINISHING: HOT DIP GALVANIZED TO BS EN ISO 1461.
6. TOLERANCES SHALL BE AS PER BS EN 40-2 UNLESS OTHERWISE SPECIFIED IN THE DRAWING
7. MAKE OF THE POLE "BAJAJ".
8. THIS HAS TO BE READ IN CONJUNCTION WITH FINAL OFFER

Sr. No.	Abbreviation	Parameters	Detail
POLES			
1	H	Height of pole.	6 Mtr.
2	T	Pole Top A/F.	70mm
3	B	Pole Bottom A/F.	130mm
4	Tk	Shaft Thickness.	3mm
5	Dh	Door Height	500mm
6	De	Door elevation	500mm
7	Bp	Base plate dim.	200x200x12mm
8	Sh	Slot / Hole dim.	24x32mm
9	Sn	No. of slot/holes.	4 nos.
10	PCD	PCD	200mm
11	S	Pole Shape/sides	Octagonal



TOLERANCES:-	
DIAMETERS A/F	± 2.5 %
POLE TOTAL LENGTH	± 1.2 %
POLE STRAIGHTNESS	± 0.3 %



REV. NO.	DATE	REVISION DESCRIPTION	DRWN	CHKD	APPRD
CLIENT:	TURNING POINT				
PROJECT:	SUPPLY OF LIGHTING POLES				
DEALER:	---				
MANUFACTURER:					
TITLE:	INDICATIVE GENERAL ARRANGEMENT DRAWING OF 6MTR OCTAGONAL POLE WITH MOUNTING ARRANGEMENT FOR DOUBLE ARM SWORD				DATE: 01-02-2024
DRWN BY:	MTP	PROJECT CODE:	DRG NO.		SHEET: 01 of 01
DSGD BY:	SK	60901	EPC-24-60901-6M OP-001		REV. NO.: 00
CHKD BY:	VA	OFFER REF. NO.:			81507
APPRD BY:	UM				

This drawing is property of "BAJAJ ELECTRICALS LTD." & must returned on request. It is submitted as confidential information in connection with enquiry, tenders, orders or contracts. It is not to be used for any other purpose or order nor may it be re-copied or lent without our authority in writing.