



P58S II series

CARICO STATICO / STATIC LOAD
2800 KG

P58F II series

CARICO STATICO / STATIC LOAD
3200 KG

MOTORI / MOTORS
4 POLI 50Hz
CARICO UTILE / LOAD CAPACITY

MOTORI / MOTORS
6 POLI 50Hz
CARICO UTILE / LOAD CAPACITY

RIDUZIONE RATIO	PULEGGIA SHEAVE DIA/mm	VELOCITÀ SPEED m/sec	HP	HP	HP	HP	HP	HP
			5 Kg	6 Kg	7 Kg	8 Kg	9 Kg	10 Kg
76:1	440	0.41-0.45	490					
	480	0.45-0.50	460					
	520	0.49-0.54	430					
	550	0.52-0.57	410					
	600	0.56-0.62	370					
	650	0.61-0.67	340					
66:1	440	0.47-0.52	460					
	480	0.52-0.57	430					
	520	0.56-0.62	400					
	550	0.59-0.65	380					
	600	0.65-0.71	350					
	650	0.70-0.77	320					
58:1	440	0.54-0.60	430	530	630			
	480	0.59-0.65	400	500	600			
	520	0.64-0.70	370	470	570			
	550	0.67-0.74	350	450	540			
	600	0.74-0.81	320	410	490			
	650	0.81-0.88	300	390	470			
52:1	440	0.60-0.66	410	510	600			
	480	0.66-0.72	380	480	580			
	520	0.71-0.78	350	440	530			
	550	0.75-0.83	330	410	500			
	600	0.82-0.90	310	380	460			
	650	0.89-0.98	290	360	440			
44:1	440	0.71-0.79	380	450	550	630		
	480	0.78-0.86	350	420	520	600		
	520	0.84-0.93	320	390	480	560		
	550	0.89-0.98	300	370	450	530		
	600	0.97-1.07	270	330	420	490		
	650	1.05-1.15	250	310	390	470		
37:1	440	0.85-0.93	370	420	490	570	630	670
	480	0.92-1.02	340	390	460	540	610	640
	520	1.00-1.10	310	350	430	500		
	550	1.06-1.17	300	330	400	470		
	600	1.15-1.27	260	300	360	430		
	650	1.24-1.36	240	280	340	400		

RIDUZIONE RATIO	PULEGGIA SHEAVE DIA/mm	VELOCITÀ SPEED m/sec	HP	HP	HP			
			4 Kg	5 Kg	6 Kg			
76:1	440	0.28-0.30	520					
	480	0.31-0.33	480					
	520	0.33-0.36	460					
	550	0.35-0.38	440					
	600	0.38-0.41	410					
	650	0.42-0.45	380					
66:1	440	0.32-0.35	500					
	480	0.35-0.38	460					
	520	0.38-0.41	440					
	550	0.40-0.44	430					
	600	0.44-0.47	400					
	650	0.48-0.52	360					
58:1	440	0.37-0.40	500	630				
	480	0.40-0.43	470	600				
	520	0.44-0.47	430	560				
	550	0.46-0.50	410	540				
	600	0.50-0.54	370	500				
	650	0.54-0.58	340	470				
52:1	440	0.41-0.44	470	600				
	480	0.45-0.48	440	570				
	520	0.49-0.52	400	530				
	550	0.51-0.55	380	510				
	600	0.56-0.60	340	470				
	650	0.61-0.65	310	440				
44:1	440	0.49-0.52	420	550				
	480	0.53-0.57	390	520	630			
	520	0.57-0.62	350	490	600			
	550	0.61-0.65	330	450	560			
	600	0.66-0.71	300	420	530			
	650	0.71-0.76	280	390	500			
37:1	440	0.58-0.62	390	550	630			
	480	0.63-0.68	360	520	590			
	520	0.68-0.73	330	480	550			
	550	0.72-0.78	310	450	490			
	600	0.79-0.85	280	420	460			
	650	0.85-0.91	260	390	430			

le tabelle fanno riferimento ad entrambi i motori