



# P70F III series

CARICO STATICO / STATIC LOAD

**8000 KG**

MOTORI / MOTORS

**4 POLI POLES 50Hz**

CARICO UTILE / LOAD CAPACITY

RIDUZIONE RATIO	PULEGGIA SHEAVE DIA/mm	VELOCITÀ SPEED m/sec	HP	HP	HP	HP	HP	HP
			14 Kg	16 Kg	18 Kg	20 Kg	22 Kg	25 Kg
<b>65:1</b>	520	0.57-0.63	1300					
	600	0.66-0.72	1100					
	650	0.71-0.78	1000					
	700	0.77-0.84	920					
<b>55:1</b>	520	0.67-0.74	1200	1450				
	600	0.78-0.86	1050	1280				
	650	0.84-0.93	950	1170				
	700	0.90-1.00	900	1080				
<b>48:1</b>	520	0.77-0.85	1100	1340	1500			
	600	0.89-0.98	960	1140	1300			
	650	0.96-1.06	880	1040	1200			
	700	1.04-1.14	800	960	1100			
<b>38:1</b>	520	0.97-1.07	960	1100	1260	1450	1500	1600
	600	1.12-1.24	830	960	1060	1250	1300	1500
	650	1.22-1.34	760	880	1000	1150	1200	1400
	700	1.31-1.45	720	800	920	1060	1100	1300
<b>54:2</b>	520	1.37-1.51		920	1040	1180	1250	1400
	600	1.58-1.74		780	900	1020	1080	1250
	650	1.71-1.89		720	820	940	980	1100
	700	1.84-2.03		660	760	860	920	1060

MOTORI / MOTORS

**6 POLI POLES 50Hz**

CARICO UTILE / LOAD CAPACITY

RIDUZIONE RATIO	PULEGGIA SHEAVE DIA/mm	VELOCITÀ SPEED m/sec	HP	HP	HP	HP	HP	HP
			8 Kg	9 Kg	10 Kg	11 Kg	12 Kg	14 Kg
<b>65:1</b>	520	0.39-0.42	1180	1260				
	600	0.45-0.48	1020	1100				
	650	0.49-0.52	940	1000				
	700	0.52-0.56	860	940				
<b>55:1</b>	520	0.46-0.49	1060	1200	1360	1460		
	600	0.53-0.57	920	1060	1180	1280		
	650	0.57-0.62	840	960	1080	1180		
	700	0.62-0.67	760	860	980	1080		
<b>48:1</b>	520	0.53-0.57	960	1100	1240	1380	1500	
	600	0.61-0.65	820	940	1060	1180	1300	
	650	0.66-0.71	740	840	960	1080	1200	
	700	0.71-0.76	660	740	860	980	1100	
<b>38:1</b>	520	0.67-0.72		880	1020	1140	1260	1500
	600	0.77-0.83		760	860	960	1060	1300
	650	0.83-0.89		700	800	900	1000	1180
	700	0.90-0.96		640	720	800	900	1060