

APF Pressure Gauges



Liquid Filled



Dry

APF Code	Dial Size	Conn (mm)	Pressure (Bar)	Fill	Entry	Case	Internal
APPGBE4016	40	1/4"	0-16		Back	Steel	Brass
APPGBE5016	50	1/4"	0-16		Back	Steel	Brass
APPGBE6316	63	1/4"	0-16		Back	Steel	Brass
APPGBE8016	80	1/4"	0-16		Back	Steel	Brass
APPGBE10016	100	1/4"	0-16		Back	Steel	Brass
APPGLE5016	50	1/4"	0-16		Lower	Steel	Brass
APPGLE6316	63	1/4"	0-16		Lower	Steel	Brass
APPGLE8016	80	1/4"	0-16		Lower	Steel	Brass
APPGLE10016	100	1/4"	0-16		Lower	Steel	Brass
APPGBESS6316	63	1/4"	0-16	Oil	Back	Stainless	Brass
APPGBESS8016	80	3/8"	0-16	Oil	Back	Stainless	Brass
APPGBESS10016	100	3/8"	0-16	Oil	Back	Stainless	Brass
APPGLESS6316	63	1/4"	0-16	Oil	Lower	Stainless	Brass
APPGLESS10016	100	3/8"	0-16	Oil	Lower	Stainless	Brass

Gauge Data

Size	1.5" , 2" , 2.5" , 3" , 4" , 4.5" , 6" , 8" , 10"
Case Types	ABS, brass, stainless steel
Window	PC, tempered glass, safety glass, plastic
Socket	Brass, stainless steel
Connection	1/8" , 1/4" , 3/8" , 1/2" (BSP, NPT, BSPT)
Measuring Range	0-16 Bar
Movement	Brass, stainless steel
Filled with liquid:	glycerine
Application	Water, air, gas, pump, compressor, regulator and fluids not corrosive to wetted parts
Options/notes	Lower or back entry, panel mount or surface mount.

