



HASCO's large range of industrial floor coating paints offer solutions suited for a wide range of requirements. Be it a busy shopping mall, an underground parking garage, an outdoor sports court, or a heavy machinery storage facility, HASCO provides the right system for your job.

Properties such as extreme chemical resistance, high impact strength, high compressive strength and thermal shock resistance are just some examples of properties HASCO flooring paints provide to insure an excellent service life, designed specifically for the project at hand.

Ease of application is also an important aspect HASCO chemists take into consideration when designing products, thus helping applicators achieve high productivity without any compromise to product quality.

The variety of high performance epoxies,
Polyurethanes, Acrylics, along with hybrid resin
systems are available to choose from within
HASCO's main line of floor coatings.



HASCO provides a diverse epoxy floor coating line. This includes crack and joint fillers, brush-able and spray-able epoxies, and self-leveling solvent free coatings.

### **HASCO**

## EPOSEAL 50

Transparent Epoxy sealer, with penetrating solvents, provides a seamless coat over concrete, as a base coat for various floor top coats.

HASCO EPOSEAL 50 also protects the integrity of concrete and prevents

dusting, and chemical degradation. Available in a moisture forgiving version, when humidity is present in concrete.

#### **HASCO**

### EPOSEAL 100

A solvent Free Epoxy sealer, used over highly porous concrete to provide a seamless seal even over degraded, uneven surfaces. Due to its odorless nature, and zero VOC content, applicators are able to use it

in confined areas. HASCO EPOSEAL 100 can also be used as a self leveling clear coat, especially over 3D printed floor designs.



## HASCO EPOXY SF 260

Solvent Free, %100 solid Epoxy Self-Leveling compound used over suitable sealers to provide self leveling floor coating up to 1 cm in thickness. HASCO EPOXY SF 260 provides very high mechanical, chemical and abrasion resistance, and can withstand very high pressure loads due to its extreme compressive strength.

# HASCO EPOXY CHEMODUR (70)

available in Solvent Free or a %70 solid version. HASCO EPOXY CHEMODUR is applied by roller or airless spray to provide a protective surface over suitable sealers to thicknesses up to 500 micron. The final result is a chemically resistant, seamless floor coating, with high abrasion and mechanical resistance.

RAL & PANTONE COLORS AVAILABLE FOR ALL HASCO FLOOR COATING TOPCOATS













HASCO provides special coatings to protect buildings and construction materials including masonry gypsum board and cement.

# HASCOTON CHEMOLAC

Vinyl Acrylic, solvent based, self-priming topcoat. Suitable for most building material and cement substrates as a non carbonating, weather stable, long lasting coat.

HASCOTON CHEMOLAC provides a breathable exterior grade topcoat. That is not affected by water, and weather conditions. This makes it particularly suitable

for marine environments as well as damp interior spaces. A three coat system of HASCOTON CHEMOLAC provides long lasting protection for up to 20 years, far exceeding conventional water-based exterior grade coatings.



effective cleaner and degreaser. HASCO LIQUICLEAN 25 is also suitable to clean road marking paint, and cautionary signs.