

NATURAL FINISH STONE SEALER

Exterior use

Water based Impregnating Sealer

For all types of natural stone & concrete paving. Suitable also for smooth honed, rough cut and polished surfaces.

Delicately enhances colour. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe.

Directions for use

SHAKE WELL BEFORE USE

Always test on an inconspicuous area prior to general application.

Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. If necessary, first wash surfaces with a dilute solution of **Pavestone Patio Cleaner** 1:10. Rinse well to remove residues and leave to dry (24hrs).

Apply generously and evenly using a light pressure sprayer, foam roller or paint brush. On more absorbent surfaces apply further coats at hourly intervals until the surface is fully saturated.

On higher porosity materials sufficient sealer should be applied until treated surfaces are fully saturated.

Any dried on and over applied sealer can be removed by rubbing with damp micro fibre cloth, or on larger areas with a rotary machine with brushes. If dried on residues are left too long and are difficult to buff away; apply a little soapy water and gently scrub with a scrubbing brush. Rinse and leave to dry.

Do not use in temperatures under 5°C or over 25°C.

Coverage: M² per coat

	1 LTR	5 LTR
Honed surfaces	30m ²	150m ²
Medium porosity surfaces	15m ²	75 m ²
High porosity surfaces	7.5m ²	37.5m ²

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 2 years for un-opened containers.

Once opened use within 6 months of purchase for optimum results.

Empty containers are recyclable. Active ingredients are water soluble and inert once cured so therefore not harmful to the environment and ecologically sound.

Health, Safety & Environmental

Ingredients: www.pavestone.co.uk/dr/naturalfinish_sealer

Keep out of reach of children.

Dispose of contents/container to hazardous or special waste collection point.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.