

<b>Product Description</b>	New generation, water based paint for decorative use on most surfaces without a primer.	
<b>Application Areas</b>	<ul style="list-style-type: none"> <li>• Degreased and/or weathered galvanized steel</li> <li>• Rust free, clean, dry mild steel</li> <li>• Wooden surfaces</li> <li>• Fabrics</li> <li>• Leather</li> <li>• Glass</li> <li>• Highly recommended for decorative areas/ furniture</li> </ul>	
<b>Product Features</b>	<ul style="list-style-type: none"> <li>• Suitable for use on degreased galvanised steel and rust free mild steel</li> <li>• Excellent adhesion</li> <li>• Excellent, no mess application properties</li> <li>• Different techniques can be used with Paint Master's Tjhoko Paint.</li> <li>• Low odor</li> <li>• Based on a water-based resin and can be diluted with water for a lime wash technique.</li> <li>• For Exterior use we recommend using Paint Master Acrylic Glaze as a top coat.</li> <li>• For Interior use we recommend using Paint Master Liquid Wax or Paint Master Acrylic Glaze as a top coat.</li> </ul>	
<b>Product Data</b>	<b>Resin Base</b>	Acrylic Emulsion
	<b>Drying Time</b>	Touch dry: 20–60 minutes Hard dry: 12 – 18 hours
	<b>Spreading Rate</b>	6.5 – 7.5 SQM per litre at 30 – 35 microns
<b>Application Details</b>		
• <b>Mixing</b>	Always stir well before use with a flat paddle.	
• <b>Application Method</b>	Air or airless spray and with brush. Foam roller application can be used	
• <b>Thinning</b>	Water (will reduce its hiding power and impair protection).	
• <b>Cleaning</b>	Application equipment cleanup is with clean tap water.	
• <b>Application</b>	<ul style="list-style-type: none"> <li>• <b>If the surface was oiled in less than 3 months, paintwork should be delayed another 3-6 months for the oil to dry.</b></li> <li>• Previously oiled or polished surfaces must be painted with Paint Master Universal Undercoat first.</li> <li>• Clean surface to remove any dust, grease, flaking, rust, oily substance.</li> <li>• Apply a generous coat of Paint Master Tjhoko Paint with a brush / roller to the area.</li> <li>• Apply as many coats as required to give the finishing desired. Minimum of two coats are required</li> <li>• Apply coats and sand depending on technique. Once desired finishing coat is apply a minimum of 24 hours is required before sealing it with Paint Master Acrylic Glaze /Paint Master Liquid Wax</li> <li>• Ready for use un-thinned, thinning with water will reduce its hiding</li> <li>• Clean application equipment with clean tap water</li> <li>• Should never be mixed with other products. This will influence its properties.</li> <li>• Do not apply before 09:00 and after 15:00 in the winter</li> <li>• Do not apply exterior if it looks like rain will occur within 6-8 hours of application</li> </ul>	
<b>Surface Preparation</b>		
• <b>Most Surfaces</b>	<ul style="list-style-type: none"> <li>• Fill all visible cracks if required.</li> <li>• Affected areas need to be cleaned to original condition by hand, mechanical or blast cleaning</li> <li>• Degrease surfaces with an abrasive Galvanized Iron Cleaner to remove the manufacturer's grease protective layer. This process is repeated until the surface is water break free</li> <li>• Lightly Sand, wipe off dust</li> <li>• If friable or powdery, seal with Paint Master Bonding or WB Plaster Primer</li> <li>• Remove dust, foreign material, fungal and algae growth</li> <li>• Remove all loose, flaking and bubbling paint</li> </ul>	
<b>Colour Range and Quantities</b>	<ul style="list-style-type: none"> <li>• This product is available in a standard range of colours and could be tinted to a desired colour on request.</li> <li>• Available in 500ml &amp; 1lt</li> </ul>	
<b>Precautions</b>	<ul style="list-style-type: none"> <li>• This product is not flammable.</li> <li>• Contains no toxic ingredients and very low VOC levels (EU regulations).</li> </ul>	
<b>Disclaimer</b>	Martin Vosloo Paints can not be held liable if the product fails due to improper surface	



# PAINT MASTER TJHOKO PAINT

TECHNICAL DATA SHEET  
APR2016

	preparation or application.
<b>Martin Vosloo Paints</b>	
011-7083166/083-2671122	martinvosloo@mweb.co.za