BAXTER RX

COMFORT AND INGENUITY

BAXTER RX, the alternative to the TWISTER model, offers total comfort thanks to its highly wrap-around frame. With its waterproof foam and ingenious system for attaching the strap, BAXTER RX offers effective protection from sprays of solids and liquids, and from dust.



CR39 and Polycarbonate lenses available.









BAXN: 39 g BAXWFSN: 15g

SUPPLIED WITH

Hard case, microfibre cloth

FRAME

• TR90

LENS MATERIAL AVAILABLE

• CR39

Polycarbonate

BAXN



Foam and strap



- **+ INCREASED PROTECTION**
- **+** WRAP-AROUND FRAME
- **WATERPROOF FOAM AND REMOVABLE STRAP**



BAXTER RX

COMFORT AND INGENUITY

| MODEL | VERSIONS | REFERENCES | SIZE | FRAME MARKING | TEMPLE LENGTH |
|-----------|------------------------|------------|-------|---------------------------|---------------|
| BAXTER RX | Worn as spectacles | BAXWFSN | 63/18 | ≌ EN166 F C€ | 122 mm |
| | Worn with foam + strap | BAXN | 63/18 | ≅ EN166 3 4 5 F C€ | 122 mm |
| | Foam + strap only kit | BAXKITFS | - | ≅ EN166 3 4 5 F C€ | - |

LENS MARKING

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power: +7/-6

Maximum cylinder compared with sphere: +/-5.

CORRECTED BASE:

Corrected base: 8

FRAME MARKING

EN 166: quaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- 3. Liquid droplets.
- 4. Large dust particles > 5 microns.
- **5.** Gas and fine dust particles < 5 microns.
- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

| PACKAGING AND EAN13 CODE | | | | | | | |
|---------------------------|---------------|---------------|---------------|--|--|--|--|
| | BAXN | BAXWFSN | BAXKITFS | | | | |
| Individual plastic bag | 3660740008314 | 3660740009489 | 3660740008000 | | | | |

| CHARACTERISTICS | | | | |
|-----------------------------------|-----------------------------|--|--|--|
| LENS MATERIALS | CR39, Polycarbonate | | | |
| TYPES OF CORRECTIONS AVAILABLE | Single vision - Progressive | | | |
| FRAME MATERIAL | TR90 | | | |
| FOAM | PC + EVA | | | |
| STRAP | NYLON | | | |













02/08/2019

Europe Bollé Safety 34 rue de la Soie 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: uk@bollebrands.com

