KURT

SPORTY AND ROBUST





SUPPLIED WITH

26 g

FRAME

Hard case, • PC/TRNZZ microfibre cloth

LENS MATERIAL AVAILABLE

- CR39
- Polycarbonate
- Trivex



- **B** SPORTY DESIGN
- **H** LARGE FRAME FOR A BETTER PROTECTION
- **H** LIGHTLY SMOKED TRANSLUCENT SIDE
- **+** ADJUSTABLE ARMED TEMPLES
- **#** WIDE FIELD OF VIEW



PXFKURT206R



SPORTY AND ROBUST

MODEL		REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
KURT	Grey/Yellow	PXFKURT206R	57/16	≅ EN166 F C€	125 mm

LENS MARKING

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

Trivex lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power: +10/-10

Maximum cylinder compared with sphere: +/-6.

CORRECTED BASE:

Corrected base: 4

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

€ European standard Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE			
	PXFKURT206R		
Per piece	3660740010072		

CHARACTERISTICS				
LENS MATERIALS	CR39, Polycarbonate, Trivex			
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive - Degressive			
FRAME MATERIALS	PC/TRNZZ			









01/04/2020

Europe Bollé Safety 34 rue de la Soie 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: uk@bollebrands.com

