



# Uniflair Air Cooled Room Cooling IDAV – IUAV – IXAV

Uniflair Direct Expansion Air Cooled Room  
Cooling with Variable Speed Drive  
compressors  
50 – 150 Kw



**Uniflair Room Cooling IDAV/IUAV/IXAV  
precision air conditioners for IT and  
mission critical applications.**

- Cooling capacity: 50 ÷ 150 kW
- Direct expansion air-cooled
- Variable Speed Drive scroll compressors
- Downflow, Upflow and Underfloor configurations
- Refrigerant R410A
- EC fans

# System Architecture: standard features

## Air filters

- Standard high efficiency EU4-pleated air filters housed in a dedicated plenum box (IDAV, IXAV models)
- Dirty filter differential pressure switch
- Low airflow differential pressure switch

## Cooling coil

- Heat exchanger coils designed for high sensible heat ratio (SHR) and reduced pressure drops
- Made from copper tubes mechanically expanded on aluminum fins
- Hydrophilic coil coating

## New microprocessor controller

- 7-inch, touch-screen LCD display interface
- Integrated management of the EEV and refrigerating circuit parameters
- Integrated Unloading logic on VSD units
- Full management of the condenser status including single fan status
- Grouping logic integrated
- RS485 and TCP/IP card bus integrated targeting the main communication protocols
- Native communication with StruxureWare system, NetBotz remote sensors
- USB and Service port integrated in the display interface



## Frame

- Self-supporting frame in galvanized steel with panels
- External panels coated with RAL9003 epoxy-polyester paint
- Internal panels with captive screws
- Internally lined with heat and sound-proofing insulation
- Refrigeration circuit inspection with unit active
- Side panels with coil inspection opening

## Brushless VSD scroll compressor

- Discharge temperature control
- High energy efficiency at partial load
- Low starting current
- No sliding contacts

## Electrical panel

- Three-phase power supply 400 V/3 Ph+N/50 Hz for all the units with a single or a double power supply
- Low voltage secondary circuit 24 Vac with isolation transformer
- Metal isolating screen for protection from live components
- General isolator with mechanical interlock
- Thermo magnetic circuit-breakers for protection
- Terminal board for no-voltage signal and control contacts

## Electronically Commuted Radical fans

- High-tech compound material impellers with optimized flow control
- High efficiency Green Tech EC motors
- Low power consumption
- High part-load efficiency
- Fan speed regulation by Modbus signal
- Regulate airflow based on actual thermal load
- Easy serviceability with quick removal kit
- Underfloor fan module (IXAV units)

# Main configurable options

## Power supply

- Single power supply
- Double power supply with automatic commutation to provide redundancy and ensure a constant power supply

## Construction options

- Downflow units (IDAV): top air return with bottom or front discharge (without additional floor stands)
- Upflow units (IUAV): front or bottom air return with top discharge
- Underfloor units (IXAV): top air return with bottom supply with multiple fan module configurations
- Standard, cleanable or low conductivity humidifier (cooling + humidification configuration)
- Condensate drain pump (cooling only and cooling + dehumidification configurations)
- Standard electrical heaters with extended fins, complete with double safety thermostat and manual resetting
- EU4 (standard) or EU5 air filters with or without motorized damper
- Power phase capacitors (not available for I\*AV1511A models)
- Energy meter and CO<sub>2</sub> emission calculator
- Automatic Floor Pressurization System through Active Floor Control (AFC)

## Additional accessories

- Suction from the top and front discharge plenums: they can be equipped with soundproofed insulation or with high efficiency air filters
- Back and top suction direct free-cooling plenum
- Floor stands (200mm height)
- Floor stands with motorized damper (500mm height)
- Motorized damper
- Adjustable baseframe (200 – 600 mm)
- Fire and smoke sensors
- Water leak detector
- Room air temperature / humidity sensor

## Fan module configurations (only IXAV models)

- Fan module with bottom supply
- Fan module with rear supply
- Fan module with front supply
- Fan module with front and side supply
- Fan module with fully open supply

## Air-cooled remote condensers (OCC)

- R410A refrigerant
- Vertical or horizontal installation
- Low-speed axial fans compliant with ERP2015
- Versions with electronically commutated (EC) motor to reduce the sound pressure level (optional)
- Fan speed regulator works exclusively via Modbus commands
- Coil protection treatment for aggressive ambient (optional)
- Low temperature versions to operate down to -40°C (optional)

# Technical data – IDAV / IUAV

IDAV models		1511A	1922A	2022A	2422A	2922A	3822A
Fan type		EC backward-curved centrifugal motor fan					
Power supply	V/ph/Hz	400 / 3ph / 50 Hz					
Fans	nr.	2	2	2	2	2	3
Air flow	m3/h	16800	16800	17000	20000	26000	27000
Gross total cooling capacity <sup>1,2</sup>	kW	65.6	76.2	80.0	108.8	124.0	156.7
Gross sensible cooling capacity <sup>1,2</sup>	kW	65.6	76.2	80.0	108.8	124.0	156.7
Fan power consumption <sup>1,2</sup>	kW	2.41	2.41	2.02	3.03	4.18	4.28
Compressor Power Consumption	kW	12.7	13.9	13.8	20.3	21.6	31.4

IUAV models		1511A	1922A	2022A	2422A	2922A	3822A
Fan type		EC backward-curved centrifugal motor fan					
Power supply	V/ph/Hz	400 / 3ph / 50 Hz					
Fans	nr.	2	2	2	2	2	3
Air flow	m3/h	16800	16800	17000	20000	26000	27000
Gross total cooling capacity <sup>1,2</sup>	kW	65.6	76.2	80.0	108.8	124.0	156.7
Gross sensible cooling capacity <sup>1,2</sup>	kW	65.6	76.2	80.0	108.8	124.0	156.7
Fan power consumption <sup>1,2</sup>	kW	2.41	2.41	2.02	3.03	4.18	4.28
Compressor Power Consumption	kW	12.7	13.9	13.8	20.3	21.6	31.4

1: Gross cooling capacities; fans must be deducted to obtain net cooling data.

2: Data refer to nominal conditions: Room at 35 °C – 30% RH, condensing temperature 45 °C.



## Dimensions

IDAV / IUAV models	1511A	1922A	2022A	2422A	2922A	3822A
Height (downflow units)	mm	2150	2150	2150	2150	2150
Height (upflow units)	mm	1950	1950	1950	1950	1950
Length	mm	1777	1777	2082	2082	2650
Depth	mm	900	900	900	900	900

# Technical data – IXAV

IXAV models		2322A	2622A	4022A
Fan type		EC backward-curved centrifugal motor fan		
Power supply	V/ph/Hz	400 / 3ph / 50 Hz		
Fans	nr.	2	2	3
Air flow	m3/h	18800	23400	30000
Gross total cooling capacity <sup>1,2</sup>	kW	107.0	121.8	166.8
Gross sensible cooling capacity <sup>1,2</sup>	kW	107.0	121.8	166.8
Fan power consumption <sup>1,2</sup>	kW	2.64	3.69	4.44
Compressor Power Consumption	kW	20.4	21.7	31.3

1: Gross cooling capacities; fans must be deducted to obtain net cooling data

2: Data refer to nominal conditions: Room at 35 °C – 30% RH, condensing temperature 45 °C.



## Dimensions

IXAV models		2322A	2622A	4022A
Height (without fan module)	mm	2150	2150	2150
Fan module height	mm	565	565	565
Length	mm	1777	2082	2650
Depth	mm	900	900	900

December 2019

[se.com/cooling](http://se.com/cooling)

Life Is On

**Schneider**  
Electric