

CA515R



HEAT-RESISTANT COWHIDE WELDER'S GLOVE

Ref. CA515R



Product specifications

Heat-resistant cowhide split leather (HR). Hand with cotton fleece lining. Cuff with canvas lining. American assembly. Length: 35 cm.

Heat-resistant treated split cowhide leather. Thickness between 1.2 and 1.4 mm.
Hand lining: batting.
Cuff lining: cotton fabric weight of 300 g/m².

COLOUR

Red

SIZE

10

Product Use - Risks



Heat



Wearing



Heavy industry

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

4: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

3: Resistance to abrasion (from 1 to 4)

1: Resistance to cutting (from 1 to 5)

3: Resistance to tear (from 1 to 4)

2: Resistance to puncture (1 to 4)

X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)

4: Resistance to flammability (from 1 to 4)

1: Resistance to contact heat (from 1 to 4)

3: Resistance to convective heat (from 1 to 4)

X: Resistance to radiant heat (from 1 to 4)

4: Resistance to small projections of liquid metal (from 1 to 4)


X: Resistance to large projections of molten metal (from 1 to 4)



EN12477:2001/A1:2005 Protective gloves for welders

TYPE A: Welding - Other welding processes - less dexterity - Type A

References

References	Bar code	COLOUR	SIZE		
CA515R10	3295249025939	Red	10	60	12