



STABILE

ALASKA S3 CI WR T0084B

CE UNI EN ISO 20345:2012 S3 CI WR SRC

Calf boot, WRU water resistant leather thickness 1,8-2,0 mm.

Lining and tongue in felt with **antibacterial** aluminium

WinTherm® safety microfilm and ANTICOLD perspiring and abrasion resistant fur.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE STABILE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

CI insulated surface against cold -17°C

WR water resistant shoe


Boot height sole included **24 cm**

Size 38-47 Shoe weight Sz 42 gr. 715


MATERIALS



TECHNOLOGIES



SECTORS



SOLE



Stabile is the comfortable alternative to the classic and "heavy" shoe for building sector.

This sole is highly performing with specific dowels, with dimensions and shapes to assure the maximum **stability**, with self-cleaning drainage channels to assure a perfect cleaning and with a soft compound to isolate the foot to the continuous **shocks**.


Line studied with a lot of attention to the technology of uppers and lightness of the materials.

ANTISLIPPING TEST RESULTS



SRA ceramic + NaLS	HEEL >= 0,28	0,42
	FLAT >= 0,32	0,44
SRB steel + glycerol	HEEL >= 0,13	0,20
	FLAT >= 0,18	0,18

PLUS



WINTHERM® SAFETY guarantees the insulation from cold of the body through the usage of two specific materials: this fibres of felt keeping the air inside the shoe and a layer of aluminium that reflects and holds the internal heat of the foot.

This antibacterial material guarantees the highest breathability, permeability and water vapor coefficient foreseen by the regulation UNI EN ISO 20345.