

TECHNICAL SPECIFICATION


GREEN LINE



Model		GL-9-1	GL-15-1	GL-15-3	GL-22-3
Power supply	/	230V~/50Hz	230V~/50Hz	380~415V/3N~/50Hz	380~415V/3N~/50Hz
Water resistance	IPX	IPX4	IPX4	IPX4	IPX4
Heating conditions - ambient temperature (DB/WB): 7/6°C, Water temperature (Input/Output): 30/35°C					
Heating capacity range	kW	3,10-8,90	5,28-14,95	5,28-14,95	7,80-22,00
Heating power input range	kW	0,58-2,10	0,98-3,85	0,98-3,85	1,48-5,90
COP A7W35		4,24-5,34	3,88-5,39	3,88-5,39	3,73-5,27
Heating conditions - ambient temperature 2°C, Water temperature (Input/Output): 30/35°C					
Cooling capacity range	kW	2,66-7,40	4,61-11,60	4,61-11,60	6,69-18,80
Cooling power input range	kW	0,55-2,01	0,95-3,60	0,95-3,60	1,45-5,50
COP A2W35		3,68-4,84	3,22-4,85	3,22-4,85	3,42-4,61
Cooling conditions - ambient temperature (DB/WB): 35/24°C, Water temperature (Input/Output): 12/7°C					
Cooling capacity range	kW	1,20-5,72	3,60-10,50	3,60-10,50	4,20-15,00
Cooling power input range	kW	0,65-2,40	1,12-4,47	1,12-4,47	1,80-7,30
Cooling current input range	A	2,9-10,5	4,9-19,6	2,0-7,9	3,2-12,9
SCOP+35 °C temperate climate		5,22	5,13	5,15	5,13
SCOP+55 °C temperate climate		3,84	3,97	3,96	3,84
Max. electric power	kW	3,0	5,3	5,3	9
Max. input current	A	13,5	24,5	10,5	15,8
Water flow	m³/h	1,0	1,7	1,7	2,9
Refrigerant / Refrigerant charge	kg	R290 / 0,50kg	R290 / 0,85kg	R290 / 0,85kg	R290 / 1,30kg
CO2 equivalent	Tonne	0,0015	0,0026	0,0026	0,0039
Sound pressure (1m)	dB(A)	42	43	44	47
Sound power level (EN12102)	dB	60	57	58	62
Net weight	kg	80	160	160	202
Working pressure (low side)	MPa	0,8	0,8	0,8	0,8
Working pressure (high side)	MPa	3,0	3,0	3,0	3,0
Device dimensions (L/W/H)	mm	1167×407×795	1287×458×928	1287×458×928	1250×540×1330
Shipping dimensions (L/W/H)	mm	1300×485×940	1420×540×1080	1420×540×1080	1380×570×1480
Compressor	Brand	HIGHLY	HIGHLY	HIGHLY	HIGHLY
Circulator pump	Brand	SHIMGE	SHIMGE	SHIMGE	SHIMGE
Ambient temperature during operation	°C	-25~43	-25~43	-25~43	-25~43
Number of fans	/	1	1	1	2
Fan motor type	/	Direct current motor	Direct current motor	Direct current motor	Direct current motor
Fan motor power range (min.-max.)	W	55~105	60~120	60~120	30~80
Fan speed (RPM)	RPM	300~600	220~600	220~600	300~750
Water connection	inch	1	1	1	1
Internal water pressure drop (max.)	kPa	20	20	20	65
Circulator pump head at nominal flow	kPa	90	85	85	100
Housing type		Galvanised sheet +ASA	Galvanised sheet +ASA	Galvanised sheet +ASA	Galvanised sheet +ASA
Recommended fuse		C16A	C25A	C16A	C16A

FoxAIR

ul. Stanisława Konarskiego 18C
44-100 Gliwice
tel: +48 727 012 921
email: info@fox-air.pro
www.fox-air.pro



ver. 4 (2022)