

PV L1 SERIES | SINGLE PHASE & DUAL MPPT

PV 4/5/6KTL-D1/G2P

Application: Residential Use



150% DC input oversizing



Fanless and noiseless



Shade smart



Remote control



Easy installation



www.primevolt.com.au

PrimeVOLT New Energy Australia Pty Ltd

Email: Info@primevolt.com.au

Address: 41C, Level 3, 650 George Street Sydney NSW 2000, Australia

Model	PV 4KTL-D1/G2P	PV 5KTL-D1/G2P	PV 6KTL-D1/G2P
Efficiency			
Max. Efficiency		98.2%	
European Efficiency	97.0%	97.3%	97.4%
Input(PV)			
Max. Input Voltage		550V	
Max. PV Configuration (STC)		150%	
Rated Input Voltage		360V	
Max. Input Current		30A (2*15A)	
Max.Short Circuit Current		40A (2*20A)	
Start Input Voltage		90V	
MPPT Operating Voltage Range		70V-540V	
Max. Number of PV Strings		2 (1/1)	
No. of MPPTs		2	
Output(Grid)			
Rated AC Active Power	4,000W	5,000W	6,000W
Max. AC Apparent Power	4,400VA	5,500VA	6,000VA
Max. AC Output Current	20A	25A	27.3A
Rated AC Voltage	220V/230V, L+N+PE		
AC Voltage Range①	160V-300V (Adjustable)		
Rated Grid Frequency	50Hz / 60Hz		
Grid Frequency Range②	45Hz-55Hz / 55Hz-65Hz (Adjustable)		
THDI	<3% (Rated Power)		
DC Current Injection	<0.5%In		
Power Factor	>0.99 Rated power (Adjustable 0.8 LD-0.8 LG)		
Protection			
DC Switch	Yes		
Anti-Islanding Protection	Yes		
AC Overcurrent Protection	Yes		
AC Short Circuit Protection	Yes		
DC Reverse Protection	Yes		
Surge Arrester	DC Type III(Type II optional) / AC Type III(Type II optional)		
Insulation Detection	Yes		
Leakage Current Protection	Yes		
General			
Topology	Transformerless		
IP Rating	IP65		
Night Self Consumption	< 1W (Standard)		
Cooling	Natural cooling		
Operating Temperature Range	-25°C-60°C		
Relative Humidity Range	0-100%		
Max. Operating Altitude	4000m		
Dimensions (W*H*D)	350mm*347mm*137mm		
Weight	8.5Kg		
HMI & COM			
Display	Wireless & APP+LED, LCD (Optional)		
Communication	Optional: WiFi / GPRS / RS485 / LAN		
Certification			
Safety	IEC62109-1, IEC62109-2		
Grid Code	DE-AR-N 4105, EN 50549-1, CEI 0-21, UNE 206001/206002-1, IEC 61727/62116, ORDINANCE n°140 2022, IEEE 1547, UL 1741, AS 4777, VDE 0126-1		
Warranty			
Country of Manufacture	China		

- Remarks :**
- ①②The range of output voltage and frequency may vary depending on different grid codes.
 - Specifications are subject to change without advanced notice.