



BPO LIGHTING

Hazardous Location LED Imports




FEATURES & SPECIFICATIONS:

Construction/Optical


- Die cast aluminum housing ensures excellent thermal dissipation
- Tempered glass lens ensures minimal lumen depreciation
- 120° distribution pattern standard, also available in 40°, 60°, 90° and 140°

Electrical System


- Maximum Output 28,000 lumens at 200 watts
- 140 lumens per watt
- Operating Temperature -40°C TO 60°C
- Driver operates at 120-277v, 50/60 Hz
- CRI > 70 at 5000K
- 5 year warranty when installed per instructions



5 Years Warranty



Long Life
50000 Hours



135lm/w

HLL-C SERIES

EXPLOSION PROOF LED

CLASS I, DIVISION 1

CLASS I, DIVISION 2

CLASS II, DIVISION 1

CLASS II, DIVISION 2

CLASS III

LISTINGS:

- UL844
- Class I, Division 1, Groups C & D
- Class I, Division 2, Groups A, B, C & D
- Class II, Division 2, Groups E, F & G
- Class III, Groups E, F & G
- UL1598A, Marine Outdoor Use
- CSA C22.2 No.137 / No. 250.0

APPLICATIONS:

- Paint Booths
- Waste Water Treatment Plants
- Shipyard Facilities
- Coastal Marine Areas
- Chemical Plants
- Pharmaceutical Plants
- Cold Storage Facilities
- Hazardous Storage Areas
- Corrosive Environments

OPTIONS:

- Various Distribution Patterns (120° Standard)
- 480V (120-277v Standard)

Hazardous Location LED Imports

www.bpolighting.com

14655 Champion Forest Dr. #1802 • Houston, Texas 77069 • (832) 977-1536

HLL-C SERIES


ORDERING INFORMATION

SERIES/LENGTH	LED WATTAGE	VOLTAGE	OPTIONS
HLL-C	***	U	
SERIES/LENGTH HLL-C	LED WATTAGE 60 = 60W (8,100 LUMENS) 80 = 80W (10,800 LUMENS) 100 = 100W (14,000 LUMENS) 150 = 150W (21,000 LUMENS) 200 = 200W (28,000 LUMENS) 250 = 250W (35,000 LUMENS)	VOLTAGE U = 120-277V (50/60 HZ) 480 = 200-480V	OPTIONS 40 = 40° DISTRIBUTION 60 = 60° DISTRIBUTION 90 = 90° DISTRIBUTION 140=140°DISTRIBUTION (120° STANDARD) 40K = 4000K (5000K STANDARD) DIM = 0-10V DIMMABLE (Special Order)


MOUNTING OPTIONS

*TRUNNION BRACKET STANDARD


*Trunnion Bracket




25° Pole Stanchion








Pole Stanchion



Wall Arm



DISTRIBUTION PATTERNS



Hazardous Location LED Imports

www.bpolighting.com

14655 Champion Forest Dr. #1802 • Houston, Texas 77069 • (832) 977-1536