



HSM SECURIO B32 - 1 x 5 mm



HSM SECURIO B32 document shredder

High quality materials, proven quality – the reliable security partner in the workplace. With an intake width of 310 mm, the document shredder effortlessly shreds DIN A3 paper. It is the perfect device for working groups.

Technical data

Order number:	1824111	Intake width:	310 mm
EAN	4026631030830	Container volume / collecting:	82 l
Cutting type:	particle cut	Collection volume in sheets (80 g):	1508
Cutting size:	1 x 5 mm	Noise level (idle operation):	ca. 56 dB(A)
Security level (DIN 66399):	F-3 P-7	Width x Depth x Height:	497 x 398 x 793 mm
Cutting capacity in sheets 80g/m²:	4	Weight:	27 kg
Power consumption:	610 W	Shredder material:	Paper
Voltage / Frequency:	220-240 V / 50 Hz		

Product information



The induction-hardened, solid steel cutting rollers guarantee durability.



Reusable cardboard box as bin for shredded material.



After opening the door, the reusable collecting bag can be easily removed and emptied.

HSM®



For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



Energy-saving

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



Automatic start/stop

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



Display bin full

The full bin is indicated via the display and the machine switches off automatically.



Filling level indication

The filling level of the waste container can be seen at all times through the inspection window.



5 year warranty on the HSM SECURIO B-series document shredders in security levels P-2 to P-5 according to ISO/IEC 21964 (DIN 66399). 3 year warranty on all other HSM SECURIO document shredders. Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).



*Nicht für / Not for HSM SECURIO B22