

GRATINGS NOT SHOWN FOR CLARITY.
FABRICATOR SHALL REMOVE HINGE PINS PRIOR TO GALVANIZING. AFTER GALVANIZING, DRILL OUT HINGES & CONFIRM HINGES WORK FREELY WITH PINS RE-INSTALLED.

GALVANIZED CHECKERED PLATE
2'-8" WIDE X 2" AND 3" LONG
1/4" THK.
ROLL TO 20" RAD.

TRIMMED
L 6 X 3 1/2 X 5/16
TOE ANGLE

GRATING

CONTINUOUS HEAVY DUTY GALVANIZED BUTT HINGE
OPEN WIDE W/
3/8" DIA. REMOVABLE PIN


5" X 1/2" THK. X 3'-0" LG. PLATE

5" X 1/2" THK. X 3'-6" LG. PLATE

DSGN/CNST

REFERENCE DRAWINGS	NO.	DATE	REVISION	BY	CHK	APPD	NO.	DATE	REVISION	BY	CHK	APPD
STD-VS-400												
STD-VS-00-00501	A	07/08	ISSUED FOR IN-HOUSE REVIEW PER EPT 37305244-02	KST	RHK	RHK						
STD-VS-00-00505	B	11/08	ISSUED FOR APPROVAL PER EPT 37305244-02	KST	RHK	RHK						
STD-VS-00-00507	C	12/08	ISSUED FOR SQUAD CHECK PER EPT 37305244-02	KST	RHK	RHK						

ENGINEERING RECORD	DATE
DRN:	KST 07/08
DSGN:	KST 07/08
CHK:	RHK 07/08
APP:	RHK 07/08
SCALE:	NONE



TITLE OF DRAWING:			
Z PAD VESSELS DETAILS LADDER & PLATFORM INLET SEPARATOR VSP-Z6011			
WORK ORDER	DRAWING NUMBER	REV	SHEET
37305244-02	VS-WPZ-00010	C	006
MODULE: 601			OF 006