



⑤ GALV. HAIL GUARD

⑥ MANUAL SHUTTERS-AC
WITH (2) GROUND LEVEL OPERATORS

2. ESTIMATED DRY WEIGHT: 46.000#
3. PAINT: H-1-S 91G49 TINT TO MATCH SW7073 "NETWORK GREY"

REV	DESCRIPTION	BY	DATE	APP'D	DATE	JOB STATUS:	CUSTOMER: VALERIUS TAG: P/N 49328 P.O. NO.: BAY0019080	Air-X-Changers Harsco	 HARSCO
						RELEASED THIS FABRICATION BEGUN		MODEL 132 F2	
								AXC JOB NO.: 090317	
								DRAWN BY: PN	DATE: 04/02/09
								CHECKED BY: BIC	DATE: 04/02/09
								DRAWING NO.: CRT	SCALE: 1:1
									0

NOTED: THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION. IT IS TO BE KEPT IN CONFIDENTIALITY AND NOT TO BE RELEASED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN CONSENT OF AIR-X-CHANGERS.

PARTS LIST



Post Office Box 1804
Tulsa, OK 74015
Phone: (918) 266-1850
Fax (918) 266-1322

JOB NUMBER: 090317

CUSTOMER: VALERUS

ORDER COVERS: (1) Model 132F2

REV.	BY	DATE	DESCRIPTION OF CHANGE
0	SCARDWELL	6/5/2009	Initiated Parts List
1	SCARDWELL	6/18/09	Revised paraflex coupling from PX120

FINISH: Valerus Standard

SURFACE PREPARATION: Chemical Clean

PRIMER: H-I-S 9267 or 92G08 Gray Primer, 1.5 TO 2.0 MILS. DFT.

FINISH COAT: AXC Std-Customer Tint: H-I-S 91G49 - Tint to match SW 7073 - Network Grey; 1.5 TO 2.0 MILS. DFT.

P.O.	QTY.	DESCRIPTION OF COMPONENTS
		NOTE: AN ASTERIK (*) IN QUANTITY COLUMN INDICATES A RECOMMENDED SPARE PART
	<u>2</u>	SECTION(S) IN ACCORDANCE WITH SPECIFICATION SHEET.
	<u>1</u>	<u>132F2</u> STRUCTURE(S), COMPLETE WITH: <u>Hail Guards - Type: Standard; Sections: EJW, AUXW; Area(Sq.Ft.): 205.7</u>
	<u>1</u>	SET SHUTTERS: TYPE <u>Manual</u> , FOR SERVICE(S) <u>AC</u> , SQ. FT. = <u>260.5</u> , #LINKAGE SETS = <u>2</u> , MOUNTING TYPE: <u>Standard</u> , EXTRA FEATURES: <u>Remote Linkage for Ground Level Operator</u>
	* <u>1</u>	FAN(S): <u>132</u> Inch DIAMETER, <u>8</u> BLADES, <u>LH</u> ROTATION, <u>MOORE-CL10K</u> MAKE, <u>8.2°</u> ANGLE @ <u>Clevis</u> , <u>3-7/16</u> Inch BORE WITH <u>7/8</u> Inch X <u>7/16</u> Inch KEYWAY, MODEL/PITCH: <u>48-HD/Manual</u> , HUB: <u>TAPER</u>
	* <u>1</u>	FAN(S): <u>132</u> Inch DIAMETER, <u>8</u> BLADES, <u>LH</u> ROTATION, <u>MOORE-CL10K</u> MAKE, <u>8.2°</u> ANGLE @ <u>Clevis</u> , <u>2-11/16</u> Inch BORE WITH <u>5/8</u> Inch X <u>5/16</u> Inch KEYWAY, MODEL/PITCH: <u>48-HD/Manual</u> , HUB: <u>TAPER</u>
	* <u>2</u>	<u>3-7/16</u> Inch DRIVE SHAFT BEARING(S), MAKE/MODEL: <u>Dodge-P2B-TAF-307R</u> , AXC P/N <u>BR1321</u>
	* <u>2</u>	<u>2-11/16</u> Inch DRIVE SHAFT BEARING(S), MAKE/MODEL: <u>Dodge-P2B-TAF-211R</u> , AXC P/N <u>BR1315</u>
	* <u>2</u>	<u>2-7/16</u> Inch IDLER BEARING(S), MAKE/MODEL: <u>Dodge-TAF/P2B-TAF-207R</u> , AXC P/N <u>BR1084</u>
	* <u>1</u>	IDLER SHAFT(S): <u>2-7/16</u> inch DIA. PER DRAWING <u>090317-SHD</u> .
	<u>1</u>	SET(S): <u>Adj. Block</u> TYPE IDLER FRAME PARTS
	* <u>1</u>	DRIVE SHAFT(S): <u>3-7/16</u> Inch DIA. PER DRAWING <u>090317-SHD</u> .
	* <u>1</u>	FAN SHAFT(S): <u>2-11/16</u> Inch DIA. PER DRAWING <u>090317-SHD</u> .
	* <u>1</u>	FAN SHAFT COUPLING(S): <u>PX140</u> MODEL, <u>3-7/16</u> Inch BORE WITH <u>7/8</u> Inch X <u>7/16</u> Inch KEYWAY ONE SIDE AND <u>2-11/16</u> Inch BORE WITH <u>5/8</u> Inch X <u>5/16</u> Inch KEYWAY ONE SIDE