PRODUCTIVITY IS THE RIGHT TOOL FOR THE JOB... FROM THE DEEPEST TOOL BOX IN THE LASER BUSINESS.

Model		Accuracy	Diameter Range	Application				
Laser Levels								
LL100N		1/8 in @ 100 ft (3.0 mm @ 30 m)	1,150 ft (350 m)	 Forms, footings and foundations (residential jobs) Septic tank or swimming pool installations Estimating cut and fill Decks and terraces 				
LL300N	<u>r</u>	3/32 in @ 100 ft (2.2 mm @ 30 m)	1,650 ft (500 m)	 Elevation control across small- and mid-size construction sites Excavations Basic slopes Leveling forms and footers Concrete pours 1 m (4 ft) marks 				
LL300S	1	1/16 in @ 100 ft (1.5 mm @ 30 m)	2,600 ft (800 m)	 General elevation control Checking and setting elevations for small to medium job sites Leveling forms and footers Estimating cut and fills Excavations Basic slopes for driveways and ramps 				
LL400HV		1/16 in @ 100 ft (1.5 mm @ 30 m)	2,600 ft (800 m)	 Checking/setting elevations, concrete forms, footings, and foundations for large commercial jobs Basic slope work such as foundations for small-to-large site prep work Excavating for forms or footers with CR600 receiver Sub-base leveling with skid steer loaders and CR600 receiver Vertical alignment 				
LL500		1/16 in @ 100 ft (1.5 mm @ 30 m)	1,600 ft (500 m)	 Checking elevations Setting concrete forms, footings, and foundations (small-to-large jobs) Ideal for larger pads Machine control compatible 				
			Grade & Universa	al Lasers				
GL412N/ GL422N	<u>n</u>	1/16 in @ 100 ft (1.5 mm @ 30 m)	2600 ft (800 m)	 Leveling concrete forms and footers Vertical alignment and plumb such as anchor bolt and form alignment Single and dual slope grading and excavating applications Grading Parking lots, tennis courts and driveways 				
GL612/ GL622		1/16 in @ 100 ft (1.5 mm @ 30 m)	2600 ft (800 m)	 Steep slope road embankments and ditch banks High accuracy grade work Wireless remote monitoring with HL750 Single and dual slope grading and excavating applications 				
UL633		1/16 in @ 100 ft (1.5 mm @ 30 m)	2600 ft (800 m)	 Dual slope grading and steep slope excavating Precision grade up to 25% in X, Y and Z axis Drift free vertical alignment and plumb Measuring slopes in open trenches and existing pipes 				
GL710/ GL720/ GL722		1/32 in @ 100 ft (0.8 mm @ 30 m)	3000 ft (900 m)	 High accuracy grade work Single and dual slope grading and excavating applications Machine control compatible General construction, site preparation and road construction 				

Laser Levels						Grade & Universal Lasers		
	LL100N	LL300N	LL300S	LL400HV	LL500	GL412N/422N	GL612/622	UL633
Laser type / classification	650 nm, Class 2	650 nm, Class 2	650 nm, Class 2	650 nm, Class 2	670 nm, Class 2	650 nm, Class 2	650 nm, Class 2/ 3 mW	650 nm, Class 3A/3R, <5mW
Self-leveling range	±5 degrees electronic servo self-leveling	±5 degrees electronic servo self-leveling	±5 degrees electronic servo self-leveling	±5 degrees electronic servo self-leveling	±11 minutes wire hung compensator	±5 degrees electronic servo self-leveling	±14 degrees electronic servo self-leveling	±14 degrees electronic servo self- leveling
Out-of-level indication	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Power source	2 x D-cell Alkaline	4 × D-cell Alkaline standard, recharge optional	4 × D-cell Alkaline standard, recharge optional	4 x D-cell Alkaline standard, NiMH optional	4 × D-cell Alkaline standard, recharge optional	4 x D-cell NiMH standard, Alkaline backup	4 x D Cell, NiMH Pack standard, Alkaline backup	4 x D Cell, NiMH Pack standard, Alkaline backup
Battery life	80 hr Alkaline	90 hr Alkaline, 45 hr NiMH	60 hr Alkaline, 47 hr NiMH	60 hr Alkaline, 47 hr NiMH	175 hr Alkaline, 100 hr NiMH	50 hr Alkaline, 35 hr NiMH	40 hr alkaline, 35 hr NiMH	40 hr alkaline, 35 hr NiMH
Grade Capability	Manual - Single axis	Manual - Single axis	Manual - Single axis	Manual - Dual Axes	No	Electronic -10 to +15% Single Axis/ Dual Axes	Electronic -25% to +25% Single Axis/ Dual Axes	Electronic -25% to +25% X, Y, Z Axis
Warranty	3 Years Limited	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years

Optical Auto Levels / Theodolites								
	AL20M	AL24A	AL24M	AL28M / AL28M-G	AL32A	DET-2		
Magnification	20x	24×	24×	28×	32x	30x		
Accuracy	+/- 2.5 mm (0.10 in)*	±2.0 mm (0.08 in)*	±2.0 mm (0.08 in)*	±1.5 mm (0.06 in)*	±1.0 mm (0.04 in)*	±50 mm (2 in)		
Aperture	30 mm (1.2 in)	30 mm (1.2 in)	30 mm (1.2 in)	30 mm (1.2 in)	36 mm (1.4 in.)	45 mm (1.8 in.)		
Shortest focus	0.6 m (1.97 ft)	0.6 m (1.97 ft)	0.6 m (1.97 ft)	0.6 m (1.97 ft)	0.6 m (1.97 ft)	1.45 m (4.76 ft)		
Compensator	Magnetic dampened	Air dampened	Magnetic dampened	Magnetic dampened	Air dampened	Automatic		
				AL28M-G available in gon				

*Note: Standard deviation according to DIN 18723 on one kilometer of double leveling

THE BROADEST LINE FROM THE STRONGEST NAME IN LASERS

An Entire industry. Invented here.

There's a reason Spectra Precision is the strongest name in the construction laser business. We invented the industry. From day one, we have pioneered every major development in laser positioning for construction. That's why you'll find over one million of our professional rotating lasers on job sites around the world... more than any other brand.

Easiest to Use

Spectra Precision instruments are engineered with state-ofthe-art components, giving you the most dependable, easiest to use, laser on the job site. Spectra Precision products are always ready to work when you are.

Best Support

Each Spectra Precision product is built with the user in mind. That is why we test and retest every laser we manufacture to assure you the most dependable, accurate laser in the world. Backed by the world's largest network of repair centers, Spectra Precision is unmatched for service, support and dependability.



YOUR LOCAL SPECTRA PRECISION LASER DEALER

Contact Information:

TRIMBLE / SPECTRA PRECISION DIVISION

5475 Kellenburger Road Dayton, Ohio 45424 U.S.A. (888) 527-3771 (Toll Free in U.S.A.) +1-937-245-5600 Phone +1-937-245-5489 Fax www.spectralasers.com

EUROPE

Trimble Kaiserslautern GmbH Am Sportplatz 5 67661 Kaiserslautern GFRMANY Tel +49-(0)6301-71 14 14 Fax +49-06301-32213



Toughest on Earth Strongest Warranty Easiest to Use

2016 CONSTRUCTION PRODUCTIVITY TOOLS

SPECTR

PRECISIO



(€ ℃

© 2016, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and Spectra Precision are trademarks of Trimble Navigation Limited registered in the United States Patent and Trademark Office and other countries. All other trademarks are the property of their respective owners. PN 022507-406B (02/2016)



LASER LEVELS

LL100N

Complete system in one caseincludes laser. HR320 receiver. rod. and tripod

Convenient storage and transportation.

Compensated self-leveling. maintains level automatically

 Maintains accuracy over the entire work area, and minimizes errors.

Robust design

 3 year no downtime warranty keeps productivity high and operating costs low.

11300N

New standard in ruggedness

Superior drop and weather protection.

Fully automatic self-leveling

Provides fast and accurate set-up.

Single axis manual slope mode via optional RC601 remote control

 RC601 makes slope matching to a single person operation.



LL300S

- Highly durable construction
- Superior drop and weather protection.

Fully automatic self-leveling

Provides fast and accurate set-up.

Extremely versatile with single-axis manual slope

 Cross-axis self-leveling allows for grade matching on the job site.



GRADE LASERS

GL412N/GL422N

Fully automatic self-leveling performs three jobs cost effectively

■ Level. -10 to +15% grade, and vertical alignment with plumb.

Full function remote control does everything you can do at the laser keypad

 Make grade changes from anywhere on the job reducing setup times.

Menu driven user interface

 Reduces learning time and eliminates complex button pressing.

GL612/GL622

Ultimate Control of X/Y Axes

• Fully automatic up to +/-25% grade on X/Y axes.

Wireless communication with the HL750 Laserometer

- Grade Matching easily measure unknown grade between two points.
- PlaneLok locks the beam to a fixed elevation or vertical alignment point for maximum stability and accuracy.

2-way full function radio remote control

 Perform all functions at the laser keypad anywhere on the job site.



GL710. GL720. GL722 Single & Dual Grade Lasers

 -0,5 to +25% grade range on the Y-axis and $\pm 10\%$ on the X-axis (GL720, GL722) with high accuracy.

Active temperature compensation

 Accurate, stable results regardless of temperature changes.

Large Alpha/Numeric Display for

- Transmitter displays are visible from ground even used on tall 10 ft (3 m) tripods.
- Grade Match, PlaneLok and Automatic Axis Alignment.
- Long range Radio Remote Control.

features

UL633

ever

LASER RECEIVERS

HR's, HL's, CR600

- Traditional laser receivers
- HR150U, HR320.
- Ideal for general exterior and interior applications.
- Models with LED's and/or LCD's.

Rod clamps are standard on all receivers

Digital Readout (DRO) receivers

- HL450, HL700, HL750, HL760,
- Digital readout of elevation.
- Exceptional durability and warranty. Advanced

features

including

Angline

radio comr






Specialty receivers

- Machine or rod mounted CR600.
- Universal receivers detect red, infrared and green beams - HL760U, HR150U.
- Line generator



The Rod-less Grade Checker

 Digital Readout receiver, Distance Meter, Tilt Sensor - All-in-One.



- Check grade from the machine cab.
- Saves labor, time, and fuel.
- Use on backhoes, excavators. dozers, box blades, trenchers. and skid steer attachments.
- RD20 in-cab display.



- All LR receivers feature
- Versatile 360 degree reception. Works with all types of rotating lasers. Multiple accuracy selections. Power options and long battery life. Ultra-bright LED's with green on-grade. LR30W-LR60W links wirelessly to the

DigiRod DR400





- each axis GL722

11400HV

Fast setup and automatic H + V self-leveling

 Minimizes operating costs and boosts productivity.

Highly durable construction

Superior drop and weather protection.

Single-axis slope mode selectable on both axes

 Provides grade matching with self-leveling cross axis.



11500

500 m (1,600 ft) working diameter

 Long-range accurate laser increases productivity by reducing the need for multiple setups on large job sites.

Built-in leveling system with out-of-level shut off

 Maintains accuracy over the entire work area and minimizes errors.

High accuracy laser. 1.5 mm per 30 m (1/16 per 100 ft) with temperature compensation

 Highly stable and repeatable accuracy even under large temperature changes



UNIVERSAL LASERS

The most versatile laser -

 Dual Grade, Horizontal. Vertical, Interior and Layout Laser based on Fan beam technology.

Fully automatic +/-25% in X. Y and Z axis Total control for any

application.

Several unique advanced

 Plane-Lok, Grade Match and Axis Alignment ensure accuracy and fast setup.

PIPE LASERS

DG613/DG813

Compact, Tough and Smart

- -12% to 40% grade range.
- High speed leveling svstem.
- Full cross axis compensation.

Wireless Remote

Long range Radio/IR remote control.

Automatic Alignment

With Spot Finder (DG813 only).



OPTICAL INSTRUMENTS

DET-2 / ALXX-A/M Series

- **Digital Electronic Theodolite**
- 2 second accuracy for all construction applications.
- Dual sided LCD with large easy to read characters.
- Rechargeable and alkaline battery packs included.

Spectra Precision Auto Levels

- 20. 24, 28 or 32 power magnification.
- Choice of air dampened or magnetic dampened.





 LR20 and adjustable LR30W for magnetic mount for general grading compact machines 3 selectable



00

accuracies

- LR50W for excavating
 LR60W for excavating and grading
- Built in blade tilt and and unique angle plumb indication

compensation



LR receivers accessories

MM-1 Magnetic Mount

- Quickly attach receivers to backhoes and excavators
- Strong dual adjustable magnet packs
- RD20 Wireless Remote Display
- Displays grade information to the operator in the cab
- Works with LR30W. LR50W. LR60W

